

**MSDS for: LN-901****Revised: 24-May-2005****SECTION 1:**

PRODUCT IDENTIFIER: LN-901 HEAVY DUTY CONSTRUCTION & REMODELING  
 DATE OF PREPARATION: JANUARY 9, 2004  
 PRODUCT USE: ADHESIVE  
 MANUFACTURED BY: MACCO ADHESIVES  
 15885 SPRAGUE RD.  
 STRONGSVILLE, OHIO 44136, U.S.A.

ICI PAINTS (CANADA)  
 8200 KEELE STREET  
 CONCORD, ONTARIO L4K 2A5, CANADA

EMERGENCY AND MSDS TELEPHONE NUMBER: 1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND TOXICOLOGY DEPARTMENT  
 ICI PAINTS NORTH AMERICA

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

<b>INGREDIENT</b>	<b>WT.%</b>
CHEMICAL NAME: 2-METHYLPENTANE COMMON NAME: 2-METHYLPENTANE CAS NUMBER: 107-83-5	10-20
CHEMICAL NAME: LIMESTONE COMMON NAME: LIMESTONE CAS NUMBER: 1317-65-3	10-20
CHEMICAL NAME: KAOLIN COMMON NAME: CLAY CAS NUMBER: 1332-58-7	20-30
CHEMICAL NAME: QUARTZ COMMON NAME: QUARTZ CAS NUMBER: 14808-60-7	0.1-1.0
CHEMICAL NAME: BENZENE, 1,3-DIETHENYL-, POLYMER WITH 1,3-BUTADIENE AND ETHENYLBENZENE COMMON NAME: STYRENE-BUTADIENE POLYMER CAS NUMBER: 26471-45-4	1-5
CHEMICAL NAME: SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC COMMON NAME: LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM) CAS NUMBER: 64742-89-8	5-10
CHEMICAL NAME: DISTILLATES (PETROLEUM), STEAM-CRACKED, POLYMERS WITH LIGHT STEAM-CRACKED PETROLEUM NAPHTHA COMMON NAME: AROMATIC HYDROCARBON RESIN CAS NUMBER: 68410-16-2	10-20

CHEMICAL NAME:	2,2-DIMETHYLBUTANE	1-5
COMMON NAME:	DIMETHYLBUTANE	
CAS NUMBER:	75-83-2	
CHEMICAL NAME:	2,3-DIMETHYLBUTANE	1-5
COMMON NAME:	DIMETHYLBUTANE	
CAS NUMBER:	79-29-8	
CHEMICAL NAME:	RESIN ACIDS AND ROSIN ACIDS, ESTERS WITH GLYCEROL	1-5
COMMON NAME:	ROSIN GLYCEROL ESTER	
CAS NUMBER:	8050-31-5	
CHEMICAL NAME:	BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE	5-10
COMMON NAME:	STYRENE-BUTADIENE POLYMER	
CAS NUMBER:	9003-55-8	
CHEMICAL NAME:	3-METHYLPENTANE	5-10
COMMON NAME:	3-METHYL PENTANE	
CAS NUMBER:	96-14-0	

### SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE: INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

#### EFFECTS OF OVEREXPOSURE

**INHALATION:** IRRITATION OF RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO LOSS OF APPETITE, MUCOUS MEMBRANE IRRITATION, FATIGUE, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, COUGHING, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, CONVULSIONS, PNEUMOCONIOSIS, LOSS OF CONSCIOUSNESS, DEATH.

**SKIN CONTACT:** IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING.

**EYE CONTACT:** IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES, SEVERE EYE IRRITATION, CORNEAL INJURY.

**INGESTION:** INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, DIFFICULTY OF BREATHING, CONVULSIONS, PARALYSIS, CARDIAC FAILURE, DEATH.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: EYE, SKIN, RESPIRATORY DISORDERS, LUNG DISORDERS

**SECTION 4: FIRST-AID MEASURES**

- INHALATION:** REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING. GET EMERGENCY MEDICAL ATTENTION. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY. REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING, HEADACHES, DIZZINESS, OR OTHER DISCOMFORT. GET MEDICAL ATTENTION IF DISCOMFORT OR IRRITATION PERSISTS.
- SKIN CONTACT:** WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE RE-USE. IF IRRITATION OCCURS, CONSULT A PHYSICIAN.
- EYE CONTACT:** FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.
- INGESTION:** IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

**SECTION 5: FIRE-FIGHTING MEASURES**

- FLASH POINT (SETA):** 1 F/ -17 C.                      **LOWER EXPLOSIVE LIMIT:** 1.0 %  
**UPPER EXPLOSIVE LIMIT:** NOT AVAILABLE
- FIRE EXTINGUISHING MEDIA:**                      DRY CHEMICAL OR FOAM, WATER FOG,  
CARBON DIOXIDE

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE. EVAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPERATURES. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK. VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES. CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE. MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT OR TOXIC GASES.

**FIRE FIGHTING PROCEDURES**

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

**HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS:**

CARBON MONOXIDE, CARBON DIOXIDE, ACRID FUMES, FORMALDEHYDE, OXIDES OF SULFUR, TOXIC GASES, SMOKE AND SOOT, OXIDES OF CALCIUM

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT. USE NON-SPARKING TOOLS. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER. COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING CLEANUP.

LARGE SPILLS: SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.

SMALL SPILLS: USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

**SECTION 7: HANDLING AND STORAGE**

HANDLING AND STORAGE: STORE BELOW 80F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

COMMON NAME: 2-METHYLPENTANE  
CAS NUMBER: 107-83-5  
ACGIH(TWA): 500 PPM  
ACGIH(STEL): C 1000 PPM

COMMON NAME: LIMESTONE  
CAS NUMBER: 1317-65-3  
ACGIH(TWA): 10 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME: CLAY  
CAS NUMBER: 1332-58-7  
ACGIH(TWA): 2 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME: QUARTZ  
CAS NUMBER: 14808-60-7  
ACGIH(TWA): .05 MG/M3 OSHA(TWA): 0.1 MG/M3

COMMON NAME: LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)  
CAS NUMBER: 64742-89-8  
OSHA(TWA): 300 PPM



COMMON NAME: DIMETHYLBUTANE  
CAS NUMBER: 75-83-2  
ACGIH(TWA): 500 PPM  
ACGIH(STEL): 1000 PPM

COMMON NAME: DIMETHYLBUTANE  
CAS NUMBER: 79-29-8  
ACGIH(TWA): 500 PPM  
ACGIH(STEL): 1000 PPM

COMMON NAME: ROSIN GLYCEROL ESTER  
CAS NUMBER: 8050-31-5  
ACGIH(TWA): 5 MG/M3

COMMON NAME: 3-METHYL PENTANE  
CAS NUMBER: 96-14-0  
ACGIH(TWA): 500 PPM  
ACGIH(STEL): 1000 PPM

#### RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING- SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION: PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS. USE EXPLOSION-PROOF EQUIPMENT. USE NON-SPARKING EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT: EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES. IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, FACE SHIELD

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.091
BOILING RANGE (F/C):	122-122/ 50- 50	WEIGHT PER GALLON:	9.09/ 10.92IMP
%VOLATILE BY VOLUME:	55.86	PHYSICAL STATE:	PASTE
APPEARANCE:	TAN	SOLUBLE IN WATER:	N
PH:	NOT APPLICABLE		

#### SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS: STABLE (SEE SECTION 5 FIRE FIGHTING MEASURES)

MATERIALS TO AVOID: OXIDIZERS, ACIDS, STYRENE MONOMER.

CONDITIONS TO AVOID: ELEVATED TEMPERATURES, CONTACT WITH  
OXIDIZING AGENT, SPARKS, OPEN FLAME, IGNITION  
SOURCES

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

#### SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME:	2-METHYLPENTANE			
CAS NUMBER:	107-83-5			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME:	LIMESTONE			
CAS NUMBER:	1317-65-3			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	6450.00 MG/KG ORL RAT			
COMMON NAME:	CLAY			
CAS NUMBER:	1332-58-7			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME:	QUARTZ			
CAS NUMBER:	14808-60-7			
CARCINOGENICITY LISTED BY:	NTP YES	IARC YES 1	OSHA NO	ACGIH NO
COMMON NAME:	LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)			
CAS NUMBER:	64742-89-8			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	> 3.16 GM/KG SKN RBT			
LD50:	> 5.00 GM/KG ORL RAT			
COMMON NAME:	AROMATIC HYDROCARBON RESIN			
CAS NUMBER:	68410-16-2			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME:	DIMETHYLBUTANE			
CAS NUMBER:	75-83-2			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME:	DIMETHYLBUTANE			
CAS NUMBER:	79-29-8			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME:	ROSIN GLYCEROL ESTER			
CAS NUMBER:	8050-31-5			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME:	STYRENE-BUTADIENE POLYMER			
CAS NUMBER:	9003-55-8			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
COMMON NAME:	3-METHYL PENTANE			
CAS NUMBER:	96-14-0			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO

**SUPPLEMENTAL HEALTH INFORMATION**

CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN.

**NOTICE:** REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO CENTRAL NERVOUS SYSTEM.

**CARCINOGENICITY:** CONTAINS CRYSTALLINE SILICA WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED CRYSTALLINE SILICA AS CARCINOGENIC TO HUMANS (GROUP 1). CRYSTALLINE SILICA IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE. THE NATIONAL TOXICOLOGY PROGRAM (NTP) HAS CLASSIFIED CRYSTALLINE SILICA AS A KNOWN HUMAN CARCINOGEN.

**REPRODUCTIVE EFFECTS:** NO REPRODUCTIVE EFFECTS ARE ANTICIPATED

**MUTAGENICITY:** NO MUTAGENIC EFFECTS ARE ANTICIPATED

**TERATOGENICITY:** NO TERATOGENIC EFFECTS ARE ANTICIPATED

**SECTION 12: ECOLOGICAL INFORMATION**

NO ECOLOGICAL TESTING HAS BEEN DONE BY ICI PAINTS ON THIS PRODUCT AS A WHOLE.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

**SECTION 14: TRANSPORT INFORMATION**

**DOT:** ADHESIVES, 3, UN1133, PGIII

**IMDG:** AEROSOLS, CLASS 2, UN1950, LIMITED QUANTITY \*\* DO NOT SHIP \*\*  
(BARRIER PACK CAN. PROPELLANT: LIQUEFIED PETROLEUM GAS, CLASS 2.1, UN 1075, FP -17 DEG C. ERG 115, EMS 2-07, MFAG TB 1 THRU 15)  
ADHESIVES, CLASS 3, UN1133, PGIII, LIMITED QUANTITY

**IATA:** CONSUMER COMMODITY, 9, ID8000

**TDG:** NOT AVAILABLE

**SECTION 15: REGULATORY INFORMATION**

SARA 302	SARA 313	CERCLA 302.4	HAZ AIR POLLUTANT	MARINE POLTNT
-------------	-------------	-----------------	----------------------	------------------

THIS PRODUCT CONTAINS NO SARA 302, CERCLA 302.4 OR HAZARDOUS AIR POLLUTANT CHEMICALS. IT ALSO CONTAINS NO CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS UNDER SARA 313. AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) & THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

**SECTION 16: OTHER INFORMATION**

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH ICI PAINTS BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. ICI PAINTS SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL. COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.