

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION					
NFPA Rating: Health-2; Flammability-1; Reactivity-0; Special-- Manufactured For: Unisource Worldwide, INC. Address: 6600 Governors Lake Pkwy Norcross, Ga 30071 Phone: 1-800-UNISOURCE		HMIS Rating: Health-2; Flammability-1; Reactivity-0; Personal Protection-B DOT Hazard Classification: ORM-D Identity (trade name as used on label): ALLSTAR ALL SHINE (U17564)			
EMERGENCY RESPONSE NUMBER: 1(888) 660-6737 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA		MSDS Number: A00135 Revision: 14 Date Prepared: 04/12/06 Prepared By: AH/IB Information Calls: (770)422-2071			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	No	5 mg/m3 (mist)	5 mg/m3 (mist)	d
PETROLEUM DISTILLATES	8052-41-3	No	100	100	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: N/A		Specific Gravity (H2O=1): Concentrate Only = 0.938			
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.50		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E		Evaporation Rate (= 1): N/E			
Solubility in Water: Partial		Water Reactive: No			
Appearance and Odor: Cream color, lemon fragrance.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols): extinguishes flame: NOT CATEGORIZED AS FLAMMABLE.		Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E		
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.		EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water fog.			
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [X] STABLE [] UNSTABLE Incompatibility (Mat. to avoid): Strong oxidizers.		HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: CO, CO2.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS					
ACUTE EFFECTS:					
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.					
Eye Contact: Slight irritation.		Skin Contact: Slight irritation.			
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.					
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Petroleum distillate has caused kidney injury in laboratory animals. Stomach and intestine irritant.					
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.					
Skin Contact: Wash with soap and water. If irritated, seek medical attention.					
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.					
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.					
Protective Gloves: Latex, if skin easily irritated.		Eye Protection: Safety glasses recommended.			
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.					
Other Protective Clothing & Equipment: None					
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH LIQUID TO SEWER.					
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.					
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.					

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only