

Balkamp Instant Gas Tank Repair .25 oz.

=====  
MATERIAL SAFETY DATA SHEET

Effective Date: none Revision Date: none

Balkamp Instant Gas Tank Repair .25 oz.

Code: LOC Page: 1  
=====

Section 1 - Product and Company Identification

PRODUCT NAME: Balkamp Instant Gas Tank Repair .25 oz.

MANUFACTURER'S NAME: EMERGENCY TELEPHONE NUMBER

Loctite Corporation (203)571-5100

Rocky Hill, CT 06067 MISCELLANEOUS INFORMATION

=====  
Section 2 - Hazardous Ingredients

Ingredients CAS No. %  
-----

Epoxy resin 25068-38-6 Unknown

Substituted aminophenol 90-72-2 Unknown

Non-hazardous ingredients Proprietary Unknown

Ingredients which have exposure limits

Exposure Limits (TWA) ACGIH OSHA OTHER

Ingredients (TLV) (PEL)  
-----

Exposure Limits (STEL) ACGIH OSHA

Ingredients (TLV) (PEL)  
-----

=====  
Section 3 - Hazards Identification

Toxicity: Possible skin and eye irritant. Possible sensitizer.

Primary Routes of Entry: Skin and eye contact, ingestion.

Signs and symptoms

of Exposure: May cause dermatitis on prolonged contact in sensitive individuals.

Existing Conditions

Aggravated by Exposure: Skin and eye conditions.

Literature Referenced Carcinogen

Ingredients Target Organ and Other Health Effects NTP IARC  
OSHA  
-----

Epoxy resin ALG IRR NO NO NO

Substituted aminophenol IRR NO NO NO

Non-hazardous ingredients No Data NO NO NO  
-----

Abbreviations

ALG Allergen IRR Irritant  
=====

MATERIAL SAFETY DATA SHEET

Effective Date: none Revision Date: none  
Balkamp Instant Gas Tank Repair .25 oz.  
Code: LOC Page: 2

=====  
Section 4 - First Aid Measures

Ingestion: Induce vomiting. Obtain medical attention.  
Inhalation: Does not apply  
Skin Contact: Wash with soap and water.  
Eye Contact: Flush at least 15 minutes with water. Obtain  
medical attention.

=====  
Section 5 - Firefighting Measures

Flash Point: More than 200 Deg. F Method: Tag Closed Cup  
Recommended  
Extinguishing Agents: Carbon dioxide, foam, dry chemical, water spray  
Hazardous Products formed  
by Fire or Thermal Decomposition Aldehydes, acids, oxides of carbon, sulfur,  
nitrogen.  
Unusual Fire or  
Explosion Hazards: None

Explosive Limits:  
(% by volume in air) Lower Not available  
(% by volume in air) Upper Not available

=====  
Section 6 - Environmental Release Measures

Steps to be taken in case  
of spill or leak: Soak up in an inert absorbent. Store in a partly  
filled, closed container until disposal.

=====  
Section 7 - Handling and Storage

Safe Storage: Store below 100 Deg. F  
  
(Contact Loctite Customer Service 1-800-243-4874 for shelf Life information)

Handling: Avoid prolonged skin contact. Keep away from eyes.  
Wash hands with soap and water after use.

=====  
Section 8 - Exposure Controls/Personal Protection

Eyes: Safety glasses or goggles.  
Skin: Polyethylene gloves.  
Ventilation: None normally needed.  
See Section 2 for Exposure Limits.

=====  
MATERIAL SAFETY DATA SHEET

Effective Date: none Revision Date: none  
Balkamp Instant Gas Tank Repair .25 oz.  
Code: LOC Page: 3

=====  
Section 9 - Physical and Chemical Properties

Appearance: Resin: Grey putty; Hardener: Black putty

Odor: Slight mercaptan  
Boiling Point: Not available  
pH: Does not apply  
Solubility in Water: Negligible  
Specific Gravity 1.9  
Volatile Organic Compound  
(EPA Method 24) 1.25%; 23.8 grams per liter  
Vapor Pressure: Not available  
Vapor Density: Not available  
Evaporation Rate  
(Ether = 1) Not available

=====  
Section 10 - Stability and Reactivity

Stability: Stable  
Hazardous Polymerization: Will not occur  
Incompatibility: None known  
Hazardous Decomposition  
Products (non-thermal): Aldehydes, acids, carbon monoxide, oxides of sulfur and nitrogen.

=====  
Section 11 - Toxicological Information

See Section 3.

=====  
Section 12 - Ecological Information

No data available

=====  
Section 13 - Disposal Considerations

Recommended methods of disposal: Incinerate following EPA and local regulations.

=====  
Section 14 - Transport Information

DOT (49 CFR 172)  
Domestic Ground Transport  
Proper Shipping Name: Unrestricted  
Hazard Class or  
Division: Unrestricted  
Identification Number: None  
Marine Pollutant: None  
IATA  
Proper Shipping Name: Unrestricted  
Class or Division: Unrestricted  
UN or ID Number: None

=====  
MATERIAL SAFETY DATA SHEET

Effective Date: none Revision Date: none  
Balkamp Instant Gas Tank Repair .25 oz.  
Code: LOC Page: 4

=====  
Section 15 - Regulatory Information

CA Proposition 65: Warning: This product contains a chemical known to the State of California to cause cancer.

Epichlorohydrin

=====  
Section 16 - Other Information

Estimated NFPA(R) Code:  
Health Hazard: 2  
Fire Hazard: 1  
Reactivity Hazard: 0  
Specific Hazard: Does not apply

Estimated HMIS(R) Code:  
Health Hazard: 2  
Flammability Hazard: 1  
Reactivity Hazards: 0  
Personal Protection: See Section 8.

NFPA is a registered trademark of the National Fire Protection Assn.  
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Stephen Repetto  
Title: Research Chemist, Environmental Health & Safety  
Company: Loctite Corp., 1001 Tr Br Cr, Rocky Hill CT 06067  
(24hr.) Phone: (860) 571-5100  
Revision Date: January 22, 1996 Revision: 0003