* Material Safety Data Sheet (MSDS)*

Balkamp Worldtech(TM) 272 Hi-Temp Threadlocker

MATERIAL SAFETY DATA SHEET Effective Date: none Revision Date: none

Balkamp Worldtech(TM) 272 Hi-Temp Threadlocker

Code: LOC Page: 1

Section 1 - Product and Company Identification

PRODUCT NAME: Balkamp Worldtech(TM) 272 Hi-Temp Threadlocker

MANUFACTURER'S NAME: EMERGENCY TELEPHONE NUMBER Loctite Corporation (203)571-5100

Rocky Hill, CT 06067 MISCELLANEOUS INFORMATION

Section 2 - Hazardous Ingredients

Ingredients CAS No. %

Aromatic dimethacrylate ester 24448-20-2 75-80

Maleimide resin 3006-93-7 10-15

CUMENE HYDROPEROXIDE* 80-15-9 1-3

Hydroxyalkyl methacrylate 27813-02-1 1-3

METHYL ALCOHOL* 67-56-1 1-3

SILICA, AMORPHOUS TREATED 112945-52-5 1-3

1-Acetyl-2-phenylhydrazine 114-83-0 0.1-1

N,N-Dialkyltoluidines 613-48-9 0.1-1

MALEIC ACID 110-16-7 0.1-1

SACCHARIN 81-07-2 0.1-1

Ingredients which have exposure limits

Exposure Limits (TWA) ACGIH OSHA OTHER Ingredients (TLV) (PEL)

^{*} This component is listed as a SARA Section 313 Toxic Chemical.

Hydroxyalkyl methacrylate None None 3 ppm

ceiling

METHYL ALCOHOL 200ppm TWA skin 200ppm TWA skin None

262 mg/m3 skin 262 mg/m3 skin

SILICA, AMORPHOUS TREATED 10 mg/m3 TWA 6 mg/m3 TWA 3 mg/m3 TWA resp. dust

Exposure Limits (STEL) ACGIH OSHA Ingredients (TLV) (PEL)

METHYL ALCOHOL 250 ppm skin 250 ppm skin

328 mg/m3 skin 325 mg/m3 skin

MATERIAL SAFETY DATA SHEET Effective Date: none Revision Date: none

Balkamp Worldtech(TM) 272 Hi-Temp Threadlocker

Code: LOC Page: 2

==========

Section 3 - Hazards Indentification

Toxicity: Mild eye irritant.

Oral LD50 more than 10000 mg/kg. Dermal LD50 more than 1500 mg/kg. Primary Routes of Entry: None known

Signs and symptoms

of Exposure: May cause dermatitis on prolonged contact in

senstitve individuals. Existing Conditions

Aggravated by Exposure: Maleimide resin: Dermatitis

Literature Referenced Carcinogen

Ingredients Target Organ and Other Health Effects NTP IARC

OSHA

Aromatic dimethacrylate ester ALG IRR NO NO NO

Maleimide resin No Data NO NO NO

CUMENE HYDROPEROXIDE ALG CNS COR IRR MUT NO NO NO

Hydroxyalkyl methacrylate ALG IRR NO NO NO

METHYL ALCOHOL EYE IRR MET NER NO NO NO

SILICA, AMORPHOUS TREATED NUI NO N/A NO

1-Acetyl-2-phenylhydrazine ALG NO NO NO

N,N-Dialkyltoluidines No Data NO NO NO

MALEIC ACID IRR NO NO NO SACCHARIN No Data YES 2B NO

Abbreviations

N/A Not Applicable 2B Possibly carcinogenic to humans ALG Allergen CNS Central nervous system COR Corrosive EYE Eyes IRR Irritant MET Metabolic MUT Mutagen NER Nervous System NUI Nuisance dust

Section 4 - First Aid Measures

Ingestion: Do not induce vomiting. Keep individual calm.

Obtain medical attention. Inhalation: Does not apply

Skin Contact: Wash with soap and water.

Eye Contact: Flush at least 15 minutes with water. Obtain

medical attention.

===========

MATERIAL SAFETY DATA SHEET Effective Date: none Revision Date: none

Balkamp Worldtech(TM) 272 Hi-Temp Threadlocker

Code: LOC Page: 3

Section 5 - Firefighting Measures

Flash Point: More than 200 Deg. F Method: Tag Closed Cup

Recommended

Extinguishing Agents: Carbon dioxide, foam, dry chemical

Hazardous Products formed

by Fire or Thermal Decomp Irritating organic vapors

Unusual Fire or

Explosion Hazards: None

Explosive Limits:

(% by volume in air)Lower 6% Methanol (% by volume in air)Upper 36% Methanol

Section 6 - Environmental Release Measures Steps to be taken in case of spill or leak: Soak up in an inert absorbent. Store in partly filled, closed container until disposal. Section 7 - Handling and Storage Safe Storage: Store below 100 Deg. F (Contact Loctite Customer Service 1-800-243-4874 for shelf Life information) Handling: Avoid prolonged skin contact. Keep away from eyes. Section 8 - Exposure Controls/Personal Protection Eyes: Safety glasses or goggles. Skin: Neoprene, rubber, or butyl rubber gloves. Ventilation: Does not apply See Section 2 for Exposure Limits. Section 9 - Physical and Chemical Properties Appearance: Red Liquid Odor: Mild Boiling Point: More than 300 Deg. F pH: Does not apply Solubility in Water: Slight

Specific Gravity 1.11 at 75 Deg. F

Volatile Organic Compound

(EPA Method 24) 8.1%; 89.9 grams per liter Vapor Pressure: Less than 5mm at 80 Deg. F

Vapor Density: Not available

Evaportation Rate

(Ether = 1) Not available

MATERIAL SAFETY DATA SHEET Effective Date: none Revision Date: none Balkamp Worldtech(TM) 272 Hi-Temp Threadlocker Code: LOC Page: 4
Section 10 - Stability and Reactivity
Stability: Stable Hazardous Polymerization: Will not occur Incompatibility: None Hazardous Decomposition Products (non-thermal): None
Section 11 - Toxicological Information
See Section 3.
Section 12 - Ecological Information
No data available
Section 13 - Disposal Considerations
Recommended methods of disposal: Incinerate following EPA and local regulations.
======================================
DOT (49 CFR 172) Domestic Ground Transport Proper Shipping Name: Unrestricted Hazard Class or Division: Unrestricted

Identification Number: None Marine Pollutant: None

IATA

Proper Shipping Name: Unrestricted Class or Division: Unrestricted

UN or ID Number: None

Section 15 - Regulatory Information

CA Proposition 65: This product contains Saccharin. No prop65 hazard warning is necessary if this product is used as reasonably anticipated.

MATERIAL SAFETY DATA SHEET Effective Date: none Revision Date: none

Balkamp Worldtech(TM) 272 Hi-Temp Threadlocker

Code: LOC Page: 5

Section 16 - Other Information

Estimated NFPA(R) Code:

Health Hazard: 1 Fire Hazard: 1 Reactivity Hazard: 1

Specific Hazard: Does not apply

Estimated HMIS(R) Code:

Health Hazard: 1

Flammability Hazard: 1 Reactivity Hazards: 1

Personal Protection: See Section 8.

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Stephen Repetto

Title: Research Chemist, Environmental Health & Safety Company: Loctite Corp., 1001 Tr Br Cr, Rocky Hill CT 06067

(24hr.) Phone: (860) 571-5100

Revision Date: January 22, 1996 Revision: 0027