

BENJAMIN MOORE & CO -- 226 ALL COLORS CHEX-WEAR EPOXY ENAMEL -- 8010-00F013309

=====
Product Identification
=====

Product ID:226 ALL COLORS CHEX-WEAR EPOXY ENAMEL

MSDS Date:03/01/1986

FSC:8010

NIIN:00F013309

MSDS Number: BJHLH

=== Responsible Party ===

Company Name:BENJAMIN MOORE & CO

Address:51 CHESTNUT RIDGE ROAD

City:MONTVALE

State:NJ

ZIP:07645

Info Phone Num:(201) 344-1200

Emergency Phone Num:(201) 344-1200

CAGE:09585

=== Contractor Identification ===

Company Name:BENJAMIN MOORE & CO

Address:51 CHESTNUT RIDGE RD

City:MONTVALE

State:NJ

ZIP:07645

Country:US

Phone:201-573-9600

CAGE:09585

Company Name:BENJAMIN MOORE & CO

Address:51 CHESTNUT RIDGE RD

Box:City:MONTVALE

State:NJ

ZIP:07645

Country:US

Phone:201-573-9600

CAGE:91950

=====
Composition/Information on Ingredients
=====

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPHTHANES
MINERAL SPIRITS

CAS:64742-88-7

Fraction by Wt: 46-49%

Other REC Limits:100 PPM

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: RESPIRATORY IRRITATION,
CENTRAL NERVOUS SYSTEM EFFECT, & ANESTHETIC. SKIN/EYES: IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: REPEATED/PROLONGED OVEREXPOSURE TO
SOLVENTS CAUSES PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE
CONTENTS MAY BE HARMFUL & FATAL.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE FROM HAZARD AREA & MAINTAIN BREATHING.
CALL PHYSICIAN. SKIN: WASH W/MILD SOAP & WATER.

=====
Fire Fighting Measures
=====

Flash Point:105F
Lower Limits:1%
Extinguishing Media:CO2, DRY CHEMICAL, WATER FOG, ALCOHOL FOAM
Fire Fighting Procedures:DON'T USE WATER STREAM ON BURNING LIQUID. COOL
EXPOSED CONTAINERS W/WATER.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. USE NON-SPARKING TOOLS TO RETURN MATERIALS TO
CONTAINER. ABSORB RESIDUE W/FULLER'S EARTH.

=====
Handling and Storage
=====

Handling and Storage Precautions:USE ONLY W/ADEQUATE VANTILATION. CLOSE
CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN. DON'T TAKE
INTERNALLY. AVOID CONTACT W/SKIN.
Other Precautions:AVOID BREATHING. KEEP AWAY FROM HEAT & FLAME.
DISCHARGE EXHAUST ONLY IN AREA AWAY FROM IGNITION SOURCES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR. USE ONLY
W/ADEQUATE VENTILATION.
Ventilation:MECHANICAL EXHAUST VENTILATION TO KEEP AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:57-61%

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:SOURCES OF IGNITION, HEAT, FLAMES
Hazardous Decomposition Products:CO2, CO

=====
Disposal Considerations
=====

Waste Disposal Methods:CONVENTIONAL PROCEDURES IN COMPLIANCE W/LOCAL,
STATE, & FEDERAL REGULATIONS. DON'T INCINERATE SEALED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.