

Sealed containers may explode if they become overheated in a fire.
Cool containers with a water mist or fog.

FIRE & EXPLOSION HAZARD:

Not sensitive to static discharge or mechanical impact.

HAZARDOUS COMBUSTION PRODUCTS:

Hazardous combustion products may include oxides of carbon and nitrogen and smoke.

SECTION V - REACTIVITY

LEVEL OF STABILITY: Stable

CONDITIONS TO AVOID: None.

INCOMPATIBILITY: Avoid oxidizing agents, strong acids and strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur.

POLYMERIZING AGENTS TO AVOID: None.

SECTION VI - TOXICOLOGICAL PROPERTIES

THRESHOLD LIMIT VALUE: Not established

EFFECTS OF EXPOSURE:

Exposure to vapour and mist is unlikely to cause health effects. Vapour concentrations are normally too low at room temperature to cause observable health effects. When spraying avoid breathing mist or back-spray. In contact with the eyes the product may cause mild irritation but is not expected to cause tissue damage. May cause irritation in prolonged contact with skin. Ingestion of the product may cause irritation of the lining of the stomach. It may also cause nausea, discomfort, CN depression and vomiting. Always use proper safety and hygiene practices as described below.

TOXICOLOGICALLY SYNERGISTIC PRODUCTS: None known.

OTHER HEALTH HAZARDS:

None of the ingredients are listed as sensitizers, reproductive toxins, teratogens or mutagens. Crystalline silica has been determined carcinogenic to humans by IARC (I) when in a respirable form. Inhalation of spray mist or sanding dust may cause lung damage.

AQUATIC TOXICITY: Not available

SECTION VII - EMERGENCY FIRST AID

In case of inhalation, remove victim to fresh air and administer artificial respiration if breathing has stopped. Obtain medical assistance immediately. In case of contact with eyes, flush with large amounts of water until irritation subsides. If irritation persists, obtain medical attention. For contact with skin, flush with large amounts of cold water. Use soap if available. Remove contaminated clothing after flushing has begun. Wash contaminated clothing before reuse. If ingested, do NOT induce vomiting. Keep at rest and obtain medical assistance immediately. If victim is conscious have victim drink 240 to 300 mL of water to dilute.

SECTION VIII - PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:

Use NIOSH approved respirator specified for protection against paint spray mist and organic vapours in restricted and confined areas. Wear coverall chemical goggles to protect against splashes. Wear solvent resistant gloves to protect hands.

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:

Dike Spill. Do NOT flush into sewers. As a general precaution, remove all sources of ignition and only use non-sparking tools. Absorb with inert material.

WASTE DISPOSAL METHODS:

Dispose of in accordance with local regulations.

STORAGE AND HANDLING:

Keep container closed when not using product. Store in cool, well-ventilated area. Keep from freezing.

SPECIAL ENGINEERING CONTROLS: Use with adequate ventilation.

=====

SECTION IX - PREPARATION INFORMATION

REGULATORY AFFAIRS DEPARTMENT
BENJAMIN MOORE & COMPANY LIMITED

January 2006

(201) 573-9600

n/e = not established

n/a = not available

=====

SECTION X - NOTICE OF DISCLAIMER

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.