



f Federal Hazard List

\* Hazardous only as dust when product is sanded.

3 Sect. 313 of the Emergency Planning & Community Right-To-Know Act of 1986

and of 40 CFR 37

n New Jersey Label Law hazardous chemical

This product may contain small amounts of materials known to the State of California to cause cancer and reproductive harm.

=====  
=====

SECTION III - PHYSICAL DATA

=====  
=====

BOILING RANGE: N/A VAPOR DENSITY: HEAVIER THAN AIR  
WEIGHT PER GAL: 9.1 - 10.8

EVAPORATION RATE: SLOWER THAN ETHER % VOLATILE VOLUME: 58.9 - 69.2

=====  
=====

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

=====  
=====

FLAMMABILITY CLASSIFICATION: NOT REGULATED FLASH PT.:  
>250 F PMCC

LEL: Not Applicable

EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:  
Closed containers may burst if exposed to extreme heat or fire.  
Toxic gases may form when product burns.

SPECIAL FIREFIGHTING PROCEDURES:  
Cool exposed containers with water. Use self-contained breathing apparatus.

=====  
=====

SECTION V - HEALTH HAZARD DATA

=====  
=====

EFFECTS OF OVEREXPOSURE - ACUTE:  
Inhalation - Irritation of the respiratory tract.  
Skin and Eye Contact - Primary irritation.  
Ingestion of large amounts could cause serious injury.

EFFECTS OF OVEREXPOSURE - CHRONIC:  
IARC has classified Carbon Black as possibly carcinogenic for humans (2B).

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

None expected when used in accordance with Safe Handling and Use Information (Section VIII).

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation - Remove to fresh air. Get medical help for any breathing difficulty. Eye Contact - Flush thoroughly with water. Call physician. Skin Contact - Wash with soap and water.

Ingestion - Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting.

Call physician.

=====

SECTION VI - REACTIVITY DATA

=====

STABILITY: STABLE HAZARDOUS POLYMERIZATION WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce carbon dioxide and carbon monoxide.

CONDITIONS TO AVOID: Elevated temperatures

INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable.

=====

SECTION VII - SPILL OR LEAK PROCEDURES

=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Flush with water. Absorb with sawdust or rags.

WASTE DISPOSAL METHOD:

Conventional procedures in compliance with local, state and federal regulations.

Do not incinerate sealed containers.

=====

SECTION VIII - SAFE HANDLING AND USE INFORMATION

=====

RESPIRATORY PROTECTION:

Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

VENTILATION:

Adequate to maintain working atmosphere below T.L.V. and L.E.L. (See Sect. II

for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.

PROTECTIVE GLOVES: Waterproof during repeated contact.

EYE PROTECTION: Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES:

Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

=====  
=====

SECTION IX - SPECIAL PRECAUTIONS

=====  
=====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not throw or drop containers.

OTHER PRECAUTIONS:

Avoid contact with eyes and prolonged contact with skin or breathing of spray mist or sanding dust. Close container after each use. Keep out of reach of children. Do not take internally.

=====  
=====

SECTION XX

=====  
=====

HMIS (Hazardous Materials Identification System) (R) NPCA

HMIS is a recognized workplace Hazard Communications System as required by OSHA (40 CFR 1910.1200). Information on establishing a complaint hazardous communication program using HMIS is available from:

American Lablemark Co., Inc., Labelmaster Division  
5724 N. Pulaski Rd., Chicago, IL 60646  
1-800-621-5808

The ratings assigned by Benjamin Moore & Co. are only suggested ratings; the contractor/ employee has ultimate responsibility for HMIS rating where this system is used.

PERSONAL PROTECTION: This code is left blank on Benjamin Moore & Co. MSDS's as it depends on application technique and the workplace ventilation. Please read Sections II through IX of this MSDS before deciding on appropriate protective

equipment and beginning work. There are codes available for this section which can be obtained from Labelmaster.  
Note: There are no SARA reportable materials in this product.