



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product name V056260
MSDS name NEVER-SEEZ REGULAR NSA-16 12.5OZ AERO
CAS number Mixture
Generic description Aerosol
Manufacturer Bostik, Inc.
211 Boston Street
Middleton , MA 01949 USA
24 hour emergency assistance Telephone: 1-800-227-0332
General assistance Telephone: 1-978-777-0100
MSDS assistance Telephone: 1-414-607-1407

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
Butane	106-97-8	5 - 10
Hexane	110-54-3	5 - 10
Propane	74-98-6	5 - 10
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	15 - 40
Heptane	142-82-5	10 - 30
Copper Powder	7440-50-8	1 - 5
Methylcyclopentane	96-37-7	1 - 5
Aluminum	7429-90-5	0.5 - 1.5

3. HAZARDS IDENTIFICATION

Emergency overview Product is a flammable aerosol. Pressurized container may explode when exposed to heat or flame. Contact may cause skin and eye irritation. Mist may cause nose and throat irritation. Ingestion may cause nausea, vomiting, pain, upset stomach, and diarrhea.

Potential health effects

Skin SKIN CONTACT: This product may cause irritation to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.

Eyes EYE CONTACT: Liquid or vapors may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly.

Inhalation INHALATION: This product may cause irritation to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination. Possibly unconsciousness and asphyxiation.

Ingestion INGESTION: This product is harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target organs Central Nervous System. Lungs. Skin. Eyes.

4. FIRST AID MEASURES

First aid

Skin For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.

Eye Immediately flush with plenty of water for at least 15 minutes, holding eyelids open at all times. Get medical attention immediately.

Inhalation Move person to non-contaminated air. If the affected person is not breathing, apply artificial respiration. Call a physician if symptoms develop or persist.

Ingestion	If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If person is conscious and can swallow, immediately give two glasses of water, but do not induce vomiting. Material is corrosive. If vomiting occurs, give fluids again. Seek immediate medical attention. Do not give anything by mouth to an unconscious or convulsing person.
Notes to physician	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately. If overexposure to the solvents in this product is suspected, testing should include nervous system and brain effects including recent memory, mood, concentration, headaches and altered sleep patterns. Liver and kidney function should be evaluated.

5. FIRE FIGHTING MEASURES

Extinguishing media	Use dry chemical, carbon dioxide, or foam. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools; this may result in frothing and increase fire intensity.
Basic fire fighting procedures	DANGEROUS when exposed to heat or flame. This material can be ignited by flame or spark under all normal atmospheric conditions. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Pressurized Container: May explode when exposed to heat or flame. Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full, or empty product containers.
Dust explosion hazard	None Known
Sensitivity to mechanical impact	Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.
Sensitivity to static discharge	Sparks generated by static discharge may ignite this product or its vapors. All containers and equipment must be bonded or grounded to minimize risk.
Unusual fire & explosion hazards	During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a buildup of internal pressures. Cool with water.
Fire fighting equipment/instructions	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Flash point	-156 °F (-104.4 °C)

Substance Name	% LEL	% UEL	Vapor Pressure (mmHG)
Heptane			53 hPa at 22.3 °C
Butane			2200 hPa at 20 °C
Propane			600-39000 hPa at 20 °C

6. ACCIDENTAL RELEASE MEASURES

Emergency action	Evacuate the area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Keep upwind of the spilled material and isolate exposure. Wear appropriate protective equipment and clothing during clean-up.
Containment	Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams. Cover spills with non-flammable absorbent and place in closed chemical waste containers.

7. HANDLING & STORAGE

For Commercial Use Only - Not Packaged or Labeled for Home Use!

Handling	Keep this product from heat, sparks, or open flame. Avoid getting this material into contact with your skin and eyes. Avoid breathing mists or aerosols of this product. Use this product with adequate ventilation. Do not reuse the empty container.
Storage	Store in a cool, dry, well-ventilated area. Do not handle or store near an open flame, heat or other sources of ignition. Keep out of direct sunlight. Do not store above 120 F (49 C).
Empty container precaution	Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended exposure limits. Explosion proof exhaust ventilation should be used.
Eye protection	Wear goggles or safety glasses with side shields.
Skin and body protection	Impervious gloves should be used at all times when handling this product. Recommended gloves include rubber, neoprene, nitrile or viton. Use of protective coveralls and long sleeves is recommended.
Respiratory protection	Avoid breathing vapor and/or mists. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA) or a supplied air respirator.
General	Eyewash fountains and emergency showers should be readily available. Use good industrial hygiene practices in handling this material.

Exposure limits

ACGIH - Threshold Limits Values - Time Weighted Averages (TLV-TWA)

Aluminum	7429-90-5	<u>10 mg/m3 TWA (metal dust)</u>
Copper Powder	7440-50-8	<u>0.2 mg/m3 TWA (fume); 1 mg/m3 TWA (dusts and mists, as Cu)</u>
Hexane	110-54-3	<u>50 ppm TWA</u>

OSHA - Vacated PELs - TWAs

Aluminum	7429-90-5	<u>15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)</u>
Copper Powder	7440-50-8	<u>0.1 mg/m3 TWA (fume, dusts, mists as Cu)</u>
Hexane	110-54-3	<u>50 ppm TWA; 180 mg/m3 TWA</u>

9. PHYSICAL & CHEMICAL PROPERTIES

Percent volatile	60 %
Solubility (H2O)	0 %
Target solids	40 %
pH	N/A
Density	1.19 g/cc
Odor threshold	N/A
Octanol/H2O coeff	N/A
Odor	Solvent
Physical state	Aerosol
Freeze protect	No
VOC (Volatile Organic Compounds)	473 g/l

10. STABILITY & REACTIVITY

Hazardous reactions/decomposition products	Upon decomposition of this product, the following oxides will be produced: Carbon dioxide, carbon monoxide, oxides of sulfur and nitrogen.
Hazardous polymerization	Will not occur.
Conditions to avoid	Keep away from sources of ignition. Avoid contact with Strong Oxidizers, Reducers, Acids and Alkalis.
Stability	Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION

LD50

Toxicology Data - Selected LD50s and LC50s

Hexane	110-54-3	<u>Inhalation LC50 Rat: 48000 ppm/4H; Oral LD50 Rat: 28710 mg/kg; Dermal LD50 Rabbit: 3000 mg/kg</u>
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	<u>Inhalation LC50 Rat: 2.18 mg/L/4H; Oral LD50 Rat: >5000 mg/kg; Dermal LD50 Rabbit: >2000 mg/kg</u>

12. ECOLOGICAL INFORMATION

VOC (Volatile Organic Compounds) 473 g/l

Ecotoxicological information Organic solvents produce slight to moderate toxicity to aquatic life. Insufficient data exists to evaluate the effect on plants, birds or land animals.

13. DISPOSAL CONSIDERATIONS

We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Waste disposal Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

14. TRANSPORT INFORMATION

DOT

Basic shipping requirements:

Proper shipping name Consumer Commodity
UN number ORM-D
Marine pollutant Yes

IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable (Heptane, BUTANE)
Hazard class 2.1
Subsidiary hazard class 9.0
UN number 1950



IMDG

Basic shipping requirements:

Proper shipping name Aerosols, flammable (HEPTANE, BUTANE)
Hazard class 2.1
UN number 1950
Marine pollutant Copper Metal Powder



15. REGULATORY INFORMATION

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200.

Federal regulations All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Copper Powder 7440-50-8 5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches); 2270 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is equal to or exceeds 0.004 inches)

Hexane 110-54-3 5000 lb final RQ; 2270 kg final RQ

CERCLA/SARA - Section 313 - Emission Reporting

Aluminum 7429-90-5 1.0 % de minimis concentration (dust or fume only)
Copper Powder 7440-50-8 1.0 % de minimis concentration
Hexane 110-54-3 1.0 % de minimis concentration

State regulations If this product contains any ingredients listed under California Proposition 65, they will be noted below:

California - Proposition 65 - Carcinogens List

Benzene 71-43-2 carcinogen, initial date 2/27/87 Trace impurity

California - Proposition 65 - Developmental Toxicity

Benzene 71-43-2 developmental toxicity, initial date 12/26/97 Trace impurity

Lithium carbonate 554-13-2 developmental toxicity, initial date 1/1/91

California - Proposition 65 - Reproductive Toxicity - Male

Benzene 71-43-2 male reproductive toxicity, initial date 12/26/97 Trace impurity

International regulations All components are included on the Canadian Domestic Substances List (DSL).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.

HMIS Ratings

Health: 1
Flammability: 4
Physical hazard: 0
Personal protection: X

SARA 311/312 HAZARD CATEGORIES

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

WHMIS status

Controlled

WHMIS labeling



WHMIS classification

A - Compressed Gas
B2 - Flammable/Combustible
D1A - Immediate/Serious-VERY TOXIC
D2A - Other Toxic Effects-VERY TOXIC
D2B - Other Toxic Effects-TOXIC

16. OTHER INFORMATION

Disclaimer

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Issue date

02/15/2006

Prepared by

Michael Simon

Supercedes

12/08/2005