



Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: Dry PTFE Lube (Aerosol)

Product Number (s): 03044

Manufactured By:

CRC Industries, Inc.
885 Louis Drive
Warminster, PA 18974
www.crcindustries.com

| | |
|----------------------------|----------------|
| General Information | (215) 674-4300 |
| Technical Assistance | (800) 521-3168 |
| Customer Service | (800) 272-4620 |
| 24-Hr Emergency (CHEMTREC) | (800) 424-9300 |

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Hazy, white suspension in liquid with alcohol odor

DANGER

Flammable. Harmful or fatal if swallowed. Contents under pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

EYE: May cause mild irritation including stinging and redness, but does not injure eye.

SKIN: Single, brief exposures may cause mild irritation. Frequent or prolonged contact may cause more severe irritation, defatting of the skin, and dermatitis.

INHALATION: High vapor concentrations are irritating to the respiratory tract and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage. Heating the dry film (> 500 F) can generate fluorine compound vapors which may lead to polymer fume fever if inhaled.

INGESTION: Low order of toxicity by ingestion. Main hazard is aspiration into the lungs during swallowing or vomiting. Small amounts aspirated into the respiratory system may cause bronchopneumonia or pulmonary adema, possible progressing to death.

CHRONIC EFFECTS: Overexposure to n-hexane may cause progressive and potentially irreversible damage to the peripheral nervous system, particularly in the arms and legs. Prolonged or repeated exposure to isopropyl alcohol may cause dry skin, low blood pressure, temporary changes in the liver, respiratory depression and effects on heart rate.

TARGET ORGANS: central nervous system, peripheral nervous system, respiratory system

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

| COMPONENT | CAS NUMBER | % by Wt. |
|-------------------------|------------|----------|
| Hexane isomers | various | 20 - 30 |
| Isopropyl alcohol | 67-63-0 | 25 - 35 |
| n-Hexane | 110-54-3 | 1.8 |
| Polytetrafluoroethylene | 9002-84-0 | < 2 |
| Liquefied petroleum gas | 68476-86-8 | 40 - 50 |

Section 4: First Aid Measures

| | |
|----------------------------|---|
| Eye Contact: | Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists. |
| Skin Contact: | Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use. |
| Inhalation: | Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician. |
| Ingestion: | DO NOT induce vomiting. Contact a physician immediately. |
| <i>Note to Physicians:</i> | Treat symptomatically. Gastric lavage using a cuffed endotracheal tube may be performed at your discretion. |

Section 5: Fire-Fighting Measures

Flammable Properties: This product is flammable in accordance with aerosol flammability definitions (16 CFR 1500.3(c)(6)).

| | | | |
|---------------------------|----------------|------------------------|-----|
| Flash Point (liquid): | < 20 F (TCC) | Upper Explosive Limit: | 9.5 |
| Flash Point (propellant): | - 156 F (est.) | Lower Explosive Limit: | 1.9 |

Suitable Extinguishing Media: Class B fire extinguishers, dry chemical, foam or CO2

Products of Combustion: fumes, smoke and carbon monoxide; fluorine compounds

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water fog or spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition. Do not spray water directly on fire; product will float and could be reignited on surface of water.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Remove all sources of ignition. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not use product near any potential source of ignition. Do not touch container to electrical sources as container will conduct electricity. Avoid contact with eyes and skin. Avoid breathing vapors.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

| COMPONENT | OSHA | | ACGIH | | OTHER | | UNIT |
|--|--------|---------|-------|--------|-------|--------|-------------------|
| | TWA | STEL | TWA | STEL | TWA | SOURCE | |
| Hexane isomers | 500(v) | 1000(v) | 500 | 1000 | NE | | ppm |
| Isopropyl alcohol | 400 | 500 (v) | 200 | 400 | NE | | ppm |
| n-Hexane | 500 | NE | 50(s) | NE | NE | | ppm |
| Polytetrafluoroethylene | NE | NE | NE | NE | 10 | mfg* | mg/m ³ |
| Carbon dioxide | 5000 | 30,000v | 5000 | 30,000 | NE | | ppm |
| N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated | | | | | | | |

* manufacturer's suggested exposure limit for dust particles

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use a NIOSH-approved cartridge respirator with an organic vapor cartridge if vapors exceed exposure limits. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVC or Viton. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid (dispensed product is dry film)

Color: hazy white suspension

Odor: alcohol

Specific Gravity: 0.73
 Initial Boiling Point: 140 F
 Freezing Point: ND
 Vapor Pressure: ND
 Vapor Density: > 1 (air = 1)
 Evaporation Rate: > 1 (Butyl acetate = 1)
 Solubility: negligible in water
 pH: NA
 Volatile Organic Compounds: wt %: 98 g/L: 715.4 lbs./gal: 5.96

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: sources of ignition, temperature extremes

Incompatible Materials: Acids, aldehydes, alkalis, amines, chlorinated hydrocarbons, ethylene oxide, halogens, isocyanates, strong acids and strong oxidizing agents

Hazardous Decomposition Products: oxides of carbon, fluorine compounds (if heated)

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

| <u>Component</u> | <u>Test</u> | <u>Result</u> | <u>Route</u> | <u>Species</u> |
|-------------------|-------------|---------------|--------------|----------------|
| Isopropyl alcohol | LD50 | 4396 mg/kg | Oral | Rat |
| n-hexane | LD50 | 28710 mg/kg | Oral | Rat |
| n-hexane | LD50 | 3000 mg/kg | Dermal | Rabbit |
| Isopropyl alcohol | LC50 | 72.6 mg/L/4H | Inhalation | Rat |
| n-hexane | LC50 | 48000 ppm/4H | Inhalation | Rat |

CHRONIC EFFECTS**Carcinogenicity:**

| | <u>Component</u> | <u>Result</u> |
|-------|------------------|---------------|
| OSHA: | None listed | |
| IARC: | None listed | |
| NTP: | None listed | |

Mutagenicity: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: n-hexane - 48 Hr EC50 water flea: 3.87 mg/L

96 Hr LC50 Lepomis macrochirus: 4.12 mg/L

Persistence / Degradability: No information available
Bioaccumulation / Accumulation: No information available
Mobility in Environment: No information available

Section 13: Disposal Considerations

Disposal: The liquid product is a RCRA hazardous waste for the characteristic of ignitability with a waste code of D001 (See 40 CFR Part 261.20 – 261.33).
Aerosol containers should be emptied and depressurized before disposal. Empty containers may be recycled. Any liquid product should be managed as a hazardous waste.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: n-hexane (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes
Reactive Hazard No
Release of Pressure Yes
Acute Health Hazard Yes
Chronic Health Hazard Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
n-hexane (1.8%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): n-hexane

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: NONE

State Right to Know:

New Jersey: 75-83-2, 110-54-3, 79-29-8
Pennsylvania: 107-83-5, 75-83-2, 110-54-3, 79-29-8, 9002-84-0
Massachusetts: 107-83-5, 75-83-2, 110-54-3, 79-29-8
Rhode Island : 110-54-3

Additional Regulatory Information: None

Section 16: Other Information

NFPA: Health: 2 Flammability: 4 Reactivity: 0
HMIS: Health: 2 Flammability: 4 Reactivity: 0 PPE: B

Prepared By: Michelle Rudnick
CRC #: 670
Revision Date: 11/02/2006

Changes since last revision: MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: Chemical Abstract Service NA: Not Applicable
ppm: Parts per Million ND: Not Determined
TCC: Tag Closed Cup NE: Not Established
PMCC: Pensky-Martens Closed Cup g/L: grams per Liter
PPE: Personal Protection Equipment lbs./gal: pounds per gallon
TWA: Time Weighted Average STEL: Short Term Exposure Limit
OSHA: Occupational Safety and Health Administration
ACGIH American Conference of Governmental Industrial Hygienists
NIOSH National Institute of Occupational Safety & Health