

PRODUCT DESCRIPTIONS

CaiKleen RBR is a precision cleaner and rejuvenator for rubber rollers and platens. Ideal for use in computers, printers, mouse roller balls, copiers, fax machines and other office and industrial equipment. Use on all rubber rollers, parts and platens. *Rejuvenates rubber and reduces misfeeds and jams!*

COMPATIBILITY

CaiKleen RBR is compatible with most materials. However, in large scale use we recommend compatibility testing for the specific applications. Contact manufacturer for guidelines and assistance. Products include odorless mineral spirits (OMS) as the carrier solvent to assist flushing away contaminants. It is slow to evaporate but non-aggressive to most materials. Once it evaporates, a thin layer of protection remains. Only thin layers are required for maximum performance.

DIRECTIONS FOR USE

Apply sparingly to rubber surface using lint-free applicator (swab, cloth or wooden stick) or with the precision needle dispenser (Part No. RBR100L-25C). If accessible, wipe off contaminants with lint-free applicator. Once clean, reapply a small amount to the rubber surface. On inaccessible areas, apply a small amount to rubber surface, wait until solvent evaporates and reapply a small amount.

N/A = Not Applicable N/E = Not Established

1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 1.1 **COMMERCIAL PRODUCT NAME (CODE NO.)**
 CaiKleen RBR, precision needle dispenser, 25ml (RBR100L-25C)
 CaiKleen RBR, dropper bottle, 59ml (RBR100L-2)
 CaiKleen RBR, bulk container, 354ml (RBR100L-12)
- 1.2 **COMPANY: CAIG Laboratories, Inc.**
 12200 Thatcher Court, Poway, California 92064 U.S.A.
 CUSTOMER SERVICE: 858/486-8388 **EMERGENCY, SPILL, LEAK, FIRE**
 PREPARED BY: Mark K. Lohkemper **OR EXPOSURE: CHEMTREC**
 REVISION DATE: 08-25-1999 1-800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

2.1 HAZARDOUS INGREDIENTS	SYMBOL(S)	C.A.S. No.	WT. % RANGE
a) Petroleum naphtha		64742-88-7	50.0%
b) Terpene hydrocarbon		5989-27-5	20%
c) Chlorinated paraffin		68440-29-9	30%

- 2.2 **OSHA HAZARDOUS COMPONENTS (29CFR1910.1200)**
 a) Petroleum naphtha, 100ppm (PEL/TWA), 100ppm(TLV/TWA)

TSCA INVENTORY: All ingredients are listed on the TSCA inventory.

EC DIRECTIVE: Complies with EC Directive 91/155/EEC

3. HAZARDS IDENTIFICATION

Flammable solvent blend. Liquid will irritate eyes and skin under repeated or prolonged exposure. Breathing high concentrations of product vapor may produce drowsiness or headache. Product may be hazardous to fish & wildlife and may contaminate waterways. California Proposition 65: The California list of chemicals, "known to cause cancer or reproductive toxicity" is so extensive it requires more clarification, research and evaluation. Meanwhile, all chemicals distributed by, or manufactured by CAIG Laboratories, shall be assumed to be on the list or contain detectable amounts of chemical listed.

4. FIRST-AID MEASURES

- 4.1 **SKIN CONTACT:** Wash with soap & water. Seek medical attention if irritation persists.
- 4.2 **EYE CONTACT:** Immediately flush with plenty of water. Remove any contact lenses and continue flushing for at least 15 minutes. Seek medical attention if irritation develops or persists.
- 4.3 **INGESTION:** Seek medical attention immediately. Induce vomiting only as directed by medical personnel.
- 4.4 **INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

5. FIRE-FIGHTING MEASURES

- 5.1 **FLASH POINT:** 60°C (140°F)
- 5.2 **FLAMMABLE LIMITS, % VOL.:** LOWER = 1.0, UPPER = 6.0
- 5.3 **HMIS LABELING:** HEALTH: 2 (moderate) FLAMMABILITY: 3 (high)
 REACTIVITY: 1 (slight)
- 5.4 **EXTINGUISHING MEDIA:** Suitable - Alcohol foam, water fog, dry chemical, CO2.
 Not to be used: Water.
- 5.5 **SPECIAL EXPOSURE HAZARDS:** Carbon dioxide, carbon monoxide, hydrocarbons.
- 5.6 **SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:** As in any fire, wear self-contained breathing apparatus and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 **PERSONAL PRECAUTIONS:** Wear respiratory protection in confined spaces and appropriate personal protective equipment; eye protection, chemically resistant gloves. Ventilate area and remove all sources of ignition.
- 6.2 **ENVIRONMENTAL PRECAUTIONS:** Avoid runoff into sewers and ditches that lead to waterways.
- 6.3 **METHODS OF CLEAN UP:** Observe recommendations for personal protective equipment detailed in Section 8. For large spills, absorb with inert material such as sand, clay or dirt and place in sealed metal container for disposal. Since products are not normally used in large quantities and product is non-hazardous, absorb with inert material and discard as you would mineral oil.

7. HANDLING AND STORAGE

- 7.1 **STORAGE:** Store in a cool, dry place, away from heat, sparks or flames. Keep container tightly closed when not in use. Do not store in direct sunlight. Keep out of reach of children.
- 7.2 **HANDLING:** Avoid prolonged or repeated contact with skin, eyes or clothing. Avoid breathing product vapor for extended periods of time. Use only with adequate ventilation. General ventilation should be adequate, but use local exhaust ventilation in confined spaces or at points of excessive discharge. Avoid activities that could cause splashing of the spilled material or create mists.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 **ENGINEERING PROTECTIVE MEASURES:** General ventilation should be sufficient to control airborne vapor levels. Local exhaust ventilation should be used if large amounts are released.
- 8.2 **PERSONAL PROTECTIVE EQUIPMENT**

RESPIRATORY PROTECTION: Full-face respirator mask equipped with acid gas/organic vapor cartridge or fume hood or other type of local exhaust ventilation.

EYE PROTECTION: Wear safety glasses, splash goggles or a full-face shield depending on the amount of exposure and likelihood of a splash hazard.

HAND PROTECTION: Wear chemically resistant rubber gloves with repeated exposure.

OTHER: None required for normal conditions of industrial use.

8.3 **INDUSTRIAL HYGIENE:** Wash hands before eating or smoking when using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 **FORM:** Flammable Liquid- see 1.1 for description

9.2 **COLOR:** clear liquid.

9.3 **ODOR:** Etheral/hydrocarbon odor.

9.4 **BOILING POINT:** 160°C.

9.5 **MELTING POINT:** N/A

9.6 **RELATIVE DENSITY:** N/E

9.7 **VAPOR PRESSURE:** <12 @ 38°C

9.8 **VAPOR DENSITY (Air=1):** N/A

9.9 **VISCOSITY (Water=1):** approx. 1

10. STABILITY AND REACTIVITY

10.1 **HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon and unburned hydrocarbons.

10.2 **CONDITIONS TO AVOID:** Do not spray around open flames, sparks, or hot metal surfaces.

10.3 **HAZARDOUS REACTIONS:** Hazardous exothermic polymerization will not occur. Not sensitive to pressure, light or shock. Will not react with water. Does not require the use of stabilizers. Will not degrade to unstable products. Change in color signifies exposure to ultraviolet light or exceeding shelf life, discard solution.

10.4 **MATERIALS TO AVOID:** Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

11.1 ROUTES OF EXPOSURE

SKIN CONTACT: Repeated or prolonged contact may cause dryness of skin, wash with soap and water and apply hand cream. Seek medical attention if irritation persists. Gloves are recommended.

EYE CONTACT: Contact with liquids, mists or vapors of this product can cause acute eye irritation, stinging and swelling.

INGESTION: Harmful if swallowed. May cause acute irritation of the linings of the mouth, nose and throat. Vomiting may result, causing aspiration of material into the lungs, with the production of chronic pulmonary edema chemical pneumonia.

INHALATION: Harmful if product vapors are inhaled in high concentrations. May cause irritation to the lining of the lungs, with subsequent chronic pulmonary edema. Acute irritation of the mouth and nasal passages may result from overexposure. Displacement of oxygen by chemical vapors may lead to drowsiness or unconsciousness.

FURTHER INFORMATION: None of the components of this product are known to have carcinogenic, mutagenic, teratogenic, sensitization effects. Breathing high vapor concentrations for long periods of time may lead to narcosis.

12. ECOLOGICAL INFORMATION

12.1 **MOBILITY:** No product-specific data is available.

12.2 **PERSISTENCE AND DEGRADABILITY:** No product-specific data available.

12.3 **BIOACCUMULATIVE POTENTIAL:** No product-specific data available.

12.4 **AQUATIC TOXICITY:** No product-specific data is available.

12.5 **OTHER DATA PERTAINING TO ECOTOXICITY:** In large quantities, water runoff may cause environmental damage.

13. DISPOSAL CONSIDERATIONS

13.1 **PREPARATION:** Product waste is suitable for fuels blending for energy recovery or disposal by incineration. Product may be recoverable by distillation or recycling. Landfilling is not recommended for disposal.

13.2 **PACKAGING:** Package, transport and dispose of in accordance with local or national regulations that apply to substances & preparations of this nature.

14. TRANSPORTATION INFORMATION

14.1 **DOT - SHIPPING NAME:** Consumer Product

CLASS: ORM-D

UN No.: Not required

14.3 **IATA -**

UN No.: ID-8000

CLASS or DIVISION: 9

LABEL: Flammable liquid

SUBSIDIARY RISK: None

14.2 **IMDG -**

SHIPPING NAME: Flammable liquid

CLASS:

UN No.:

IMDG CODE:

LABEL: Not required

PACKAGING INSTRUCTIONS: 910

EMS: Chemtrec-USA

MFAG NO.: #RBR100L

MARINE POLLUTANT: No

15. REGULATORY INFORMATION

EC HAZARD WARNING LABEL

Symbol and Classification: F Highly flammable

Risk Phrases: Highly flammable, Harmful if swallowed

Safety Phrases: Keep away from sources of ignition - No smoking. Avoid contact with eyes. In case of insufficient ventilation, wear suitable respiratory equipment. Keep out of reach of children. Contains: petroleum naphtha solvent.

To be disposed of as hazardous waste. Users should also refer to any local or national regulations that apply to substance or preparations of this nature.

16. OTHER INFORMATION:

ENVIRONMENTAL IMPACT DATA (percent by weight)

CFC: 0.0%

HCFC: 0.0%

CL.SOLV.: 0.0%

VOC: 70%

HFC: 0.0%

ODP: 0.0%

All information and data contained in this literature are believed to be accurate, however, it should not be taken as definitive for all users. All materials may present unknown hazards and should be used with caution. Improper use can cause damage to products and to individuals health. Users should thoroughly test advertised products in their application, and independently determine satisfactory results before use in large scale production or manufacturing processes.

Additional Information Sheets

B-SB1

C-PG100

C-D100

C-MCL100

SB-G100

SB-DP100

SB-DIR

SB-AE

SB-Q&A

SB-SPEC

CAIG Product Line Brochure

Product Information - ProGold

Product Information - DeoxIT

Product Information - CalLube MCL

TECH INFO on ProGold

TECH INFO on DeoxIT & PreservIT

Directions For Use

Application Examples (Uses in industry)

Questions & Answers

Specifications, Comparisons & Compatibility



12200 Thatcher Court
Poway, CA 92064 U.S.A.

TEL: 858 / 486-8388 FAX: 858 / 486-8398

Email: caig123@aol.com WebSite: www.caig.com