

Material Safety Data Sheet

U.S. Department of Labor

May be used to comply with

OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

Occupational Safety and Health
Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List
48K Scrubby Perm. Laundry Marker, #7480R
& 7480B series, Buffalo Laundry Marke., T-Shirt
Marker, Fabric Fun36815,86488,86558

Note: Blank spaces are not permitted. If any item is
not applicable, or no information is available, the
space must be marked to indicate that.

Section I

Manufacturer's Name: Dri Mark Products Inc.	Emergency Telephone Number 1-516-484-6200
Address (Number, Street, City, State, and ZIP Code) 15 Harbor Park Dr.	Telephone Number for Information 1-516-484-6200
Pt. Washington, New York 11050	Date Prepared 1/24/200
	Signature of Preparer (optional) Roberta Dobbs

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS#	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
N. Propyl Alcohol	CAS# 71-23-8			200PPM	
Ethyl Alcohol	CAS# n/a			200P (depends on color)	
Ethyl Acetate 99%	CAS# 141-78-6			400PPM	
Diethylene Glycol Monobutyl Ether	CAS # 112-34-5			None Established	
Poly Ethylene Glycol	CAS# 25322-68-3			None Established	
Rosin	CAS# 65997-11-7			None Established	
Dyes (Depends on color)	Mixture			None Established	

Section III - Physical/Chemical Characteristics

Boiling Point	196°F	Specific Gravity (H ₂ O = 1)	0.88
Vapor Pressure (mm Hg.)	Not Estab.	Melting Point	
Vapor Density (AIR = 1)	Not Estab.	Evaporation Rate (Butyl Acetate = 1)	Approx. 1.65
Solubility in Water: Soluble in water			
Appearance and Odor : Colored with very faint odor			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): Unknown	Flammable Limits: Non-Flammable	LEL; N/A	UEL; N/A
Extinguishing Media: CO ₂ , Water, Foam			
Special Fire Fighting Procedures: Standard fire fighting Equipment			
Unusual Fire and Explosion Hazards None. Liquid Ink is Flammable			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid: Avoid inhaling, swallowing,
	Stable:	X	
Incompatibility (<i>Materials to Avoid</i>) None			
Hazardous Decomposition or Byproducts Thermal Decomposition may cause unknown organics			
Hazardous Polymerization	May Occur		Conditions to Avoid: None
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?: N/A	Skin?: N/A	Ingestion? : N/A
Health Hazards (<i>Acute and Chronic</i>) none			
Carcinogenicity: No known effects	NTP?: N/A	IARC Monographs?: N/A	OSHA Regulated?: No
Signs and Symptoms of Exposure: None, Since the ink is soaked in a porous reservoir inside a non reactive vessel, there is no likelihood of over exposure.			
Medical Conditions none			
Emergency and First Aid Procedures Remove to fresh air, call physician			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled: As the product is soaked in a porous reservoir. There is no possibility of spillage.
Waste Disposal Method: Dispose of in accordance with local government requirements .
Precautions to Be taken in Handling and Storing: Store in a cool dry area. Keep container tightly closed
Other Precautions:: Avoid contact with eyes and skin. Do not inhale. Close the cap when not in use. Not intended for children.

--

Section VIII - Control Measures

Respiratory Protection (<i>Specify Type</i>) Avoid Inhalation, no additional protection required.		
Ventilation	Local Exhaust: No	Special: None
	Mechanical (<i>General</i>): No	Other: None
Protective Gloves: No		Eye Protection: Avoid contact with eyes
Other Protective Clothing or Equipment: None		
Work/Hygienic Practices: Avoid contact with skin and eyes. Wash hands after use.		