

---

**SECTION I - Material Identity**

---

Item Name	
Part Number/Trade Name	DURABOND ADHESIVE - D-3001
National Stock Number	8040PMCNERG165
CAGE Code	<u>90300</u>
Part Number Indicator	A
MSDS Number	148367
HAZ Code	B

---

**SECTION II - Manufacturer's Information**

---

Manufacturer Name	DAP INC
P.O. Box	277
City	DAYTON
State	OH
Country	US
Zip Code	45401
Emergency Phone	800-543-3840 INFO 513-667-4461

---

**MSDS Preparer's Information**

---

Date MSDS Prepared/Revised	13JAN94
Active Indicator	N

---

**Alternate Vendors**

---

---

**SECTION III - Physical/Chemical Characteristics**

---

Specification Number	N/R
Appearance/Odor	OFF-WHITE PASTE WITH SWEET ODOR
Boiling Point	212 F
Specific Gravity	1.5
Solubility in Water	NE
Container Pressure Code	4
Temperature Code	8
Product State Code	U

---

#### SECTION IV - Fire and Explosion Hazard Data

---

Flash Point Method	SCC
Extinguishing Media	FOAM, CARBON DIOXIDE, DRY CHEMICAL
Special Fire Fighting Procedures	NONE KNOWN
Unusual Fire/Explosion Hazards	USE WATER SPRAY TO COOL EXPOSED CONTAINERS

---

#### SECTION V - Reactivity Data

---

Stability	YES
Stability Conditions to Avoid	EXCESSIVE HEAT AND FREEZING
Materials to Avoid	STRONG OXIDIZERS AND CAUSTICS
Hazardous Decomposition Products	NORMAL COMBUSTION PRODUCTS
LD50 - LD50 Mixture	N/R

---

#### SECTION VI - Health Hazard Data

---

Route of Entry: Skin	YES
Route of Entry: Inhalation	YES
Health Hazards - Acute and Chronic	MAY IRRITATE EYES, SKIN, NOSE & RESP TRACT. HARMFUL IF INHALED. HARMFUL OR FATAL IF SWALLOWED. IF INGESTED CAUSES VOMITING, DIARRHEA AND DEPRESSED RESP. INHALATION MAY EFFECT THE BRAIN OR NERV SYS CAUSING DIZZINESS, HEADACHE, OR NAUSEA
Carcinogenity: NTP	YES
Carcinogenity: IARC	N/R
Carcinogenity: OSHA	N/R
Symptoms of Overexposure	REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED EXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYS DAMAGE. INGESTION OF ETHYLENE GLYCOL IN EXCESS MAY LEAD TO RESP AND CARDIAC FAILURE, KIDNEY AND LIVER DAMAGE
Medical Cond. Aggravated by Exposure	NONE KNOWN
Emergency/First Aid Procedures	EYE: FLUSH WITH WATER FOR 15 MIN, CONTACT PHYSICIAN IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. INHAL: REMOVE

TO FRESH AIR. INGEST: DO NOT  
INDUCE VOMITING. CONTACT  
PHYSICIAN OR POISON CONTROL  
IMMEDIATELY

---

## SECTION VII - Precautions for Safe Handling and Use

---

Steps if Material Released/Spilled	USE ABSORBENT MATERIAL OR SCRAPE UP DRIED MATERIAL AND PLACE INTO CONTAINERS
Waste Disposal Method	DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS
Handling and Storage Precautions	STORE AWAY FROM CAUSTICS AND OXIDIZERS. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP CONTAINERS FROM EXCESSIVE HEAT AND FREEZING
Other Precautions	INTENTIONAL MISUSE BY BELIBERATELY CONCENTRATING AND INHALING VAPORS MAY BE HARMFUL OR FATAL

---

## SECTION VIII - Control Measures

---

Respiratory Protection	IF TLV IS EXCEEDED, USE NIOSH/OSHA RESPIRATOR
Ventilation	SUFFICIENT MECHANICAL VENT (LOCAL OR GENERAL EXHAUST)
Protective Gloves	SOLVENT IMPERVIOUS GLOVES
Eye Protection	SAFETY W/SIDE SHIELDS OR GOGGLES
Other Protective Equipment	W
Work Hygenic Practices	WASH CONTAMINATED CLOTHING BEFORE REUSE
Supplemental Health/Safety Data	1ST AID-EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SEEK MD. SKIN: WASH W/ SOAP & WATER. INHAL: REMOVE TO FRESH AIR. SEEK MD. INGEST: DO NOT INDUCE VOMITING. SEEK MD OR REGIONAL POISON CONTROL CENTER. IMMEDIATELY
Disposal Code	0

---

## SECTION IX - Label Data

---

Protect Eye	YES
-------------	-----

Protect Skin	YES
Protect Respiratory	YES
Chronic Indicator	YES
Contact Code	SLIGHT
Fire Code	UNKNOWN
Health Code	UNKNOWN
React Code	UNKNOWN

---

### SECTION X - Transportation Data

---

Container Quantity	1
Unit of Measure	QT

---

### SECTION XI - Site Specific/Reporting Information

---

---

### SECTION XII - Ingredients/Identity Information

---

Ingredient #	01
Ingredient Name	MINERAL SPIRITS
CAS Number	64742887
Proprietary	NO
Percent	5
OSHA PEL	100 PPM TWA
ACGIH TLV	100 PPM TWA
Ingredient #	02
Ingredient Name	ETHYLENE GLYCOL
CAS Number	107211
Proprietary	NO
Percent	3
OSHA PEL	50PPM CEILING