

**MATERIAL SAFETY DATA SHEET****MSDS # 80001****Section One: Identification**

Sanford, L.P.  
2707 Butterfield Road  
Oak Brook, IL 60523 USA  
800-323-0749 or 630-481-2000

EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name: Expo Low Odor Dry Erase Markers

Colors: All Colors, except Pink

Sanford is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the AP Non Toxic Seal. Products bearing the AP Approved Product Seal of The Art and Creative Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute Toxicology Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans, or to cause acute toxicity or chronic health problems.

**Section Two: Hazard Identification**

This product is considered safe under normal use conditions.

**Section Three: Composition**

Ethanol (64-17-5), isopropyl alcohol (67-63-0), butanol ((71-36-3), pigments and resins, release agent, additives

**Section Four: First Aid Measures**

Inhalation: This product is considered safe under normal use conditions.

Skin Contact: This product is considered safe under normal use conditions.

Eye Contact: This product is considered safe under normal use conditions.

Ingestion: This product is considered safe under normal use conditions.

**Section Five: Fire Fighting Measures**

Flash Point: 66F (TOC)

Flammability Limits (% by volume): Lower: 3.3% Upper: 19.0%

Extinguishing Media: As appropriate for surrounding area.

Special Fire Fighting Measures: None

Unusual Fire and Explosion Hazards: None

**Section Six: Accidental Release Measures**

In Case of Spill or Accidental Release: Wipe up with absorbent material.

**Section Seven: Handling and Storage**

Handling: Do not shake marker.

Storage: Keep cap on marker when not in use. Store markers horizontally.

**Section Eight: Exposure Controls and Personal Protection**

Eye Protection: None under normal use conditions.

Clothing: None under normal use conditions.

Respirator: None under normal use conditions.

Ventilation: None under normal use conditions.

**Section Nine: Physical and Chemical Properties**

**For ink unless otherwise specified:**

Boiling Point: 79C (ethanol)  
 Specific Gravity: ~1  
 Vapor Pressure: Not determined  
 Solubility in Water: Miscible  
 Evaporation Rate: Not determined  
 Appearance/Odor: Colored ink; alcoholic odor

**Section Ten: Stability and Reactivity**

Stability: Stable  
 Conditions to Avoid: None known  
 Chemical Incompatibility: None known  
 Hazardous Decomposition: None known  
 Hazardous Polymerization: Will not occur

**Section Eleven: Toxicological Information**

See Section Two: Hazard Identification for any hazards

**Section Twelve: Ecological Information**

Not available

**Section Thirteen: Disposal Considerations**

Dispose in accordance with Federal, State, and Local Regulations.

**Section Fourteen: Transport Information**

DOT: Not regulated  
 IATA: Not regulated  
 IMO: Not regulated

**Section Fifteen: Regulatory Information**

TSCA: The product listed on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory

**Section Sixteen: Other Information**

**HMIS Code**

Health	N/A
Flammability	N/A
Reactivity	N/A
Personal Protection	N/A

**0=Minimal / 4 = Severe**

Sanford has been advised by Counsel that the OSHA Hazard Communication Standard does not apply to the Sanford Product described in this Material Safety Data Sheet. The reason for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2006 per the Code of Federal Regulations. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by the Hazard Communication Standard nor is this MSDS meant to comply with all requirements of the Hazard Communication Standard.