

FP220 G

MATERIAL SAFETY DATA SHEET
For Coatings, Resins and Related Materials

09/16/33

SECTION I - PRODUCT IDENTIFICATION

Manufacturer: RICO COATINGS, INCORPORATED
P.O. BOX 1003
COLLIER ROAD
TODDGA
Product Class: 01
Trade Name : CLEAR BASE
Product Code : #L-449
D.A.S. Number:

Information Phone: (404)-886-2189
Emergency Phone: (404)-886-2189

GA 30577
Hazard Ratings:
! none -> extreme Health - 3
! 0 -> 4 Fire - 3
Reactivity - 0

Fungicidal
Sealer

SECTION II - HAZARDOUS INGREDIENTS

Ingredients	CAS #	Weight %	Exposure Limits	Vapor Pr. (lb/Hr)
XYLENE	1330-20-7	17.	100, PPM	9.5
ISOBUTYL ACETATE	110-19-0	15.	150, PPM	12.5
GLYCOL ETHER ESTER	111-15-9	7.5	5, PPM	6.
TOLUENE	108-88-3	1.9	200, PPM	38.
BETONS	67-64-1	48.	1000, PPM	190.

SECTION III - PHYSICAL DATA

Boiling Point: 132 - 284 Deg. F
Specific Gravity: 3.84 x n-Butyl Acetate
Vapor Density: Heavier than Air.
Liquid Density: Lighter than Water.
Weight per gallon: 7.2 Pounds.
Appearance: CLEAR LIQUID

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Hazard Class:
Flushing Media:
Flash Point: -4 F tcc LEL: 1.
FIRE FIGHTING PROCEDURES:
WATER, CARBON DIOXIDE OR DRY CHEMICAL,
FOAM, WATER SPRAY MAY BE INEFFECTIVE. WATER SHOULD
BE USED TO COOL CONTAINERS.
FIRE & EXPLOSION HAZARDS:
This material is highly flammable and may cause
material from heat, sparks and open flames.

SECTION V - HEALTH HAZARD DATA

EXPOSURE LEVEL:
OVEREXPOSURE:
SYMPTOMS: HEADACHE, NAUSEA OR IMPAIRED REACTION
TIME AND COORDINATION
CONTACT: PROLONGED OR REPEATED CONTACT MAY CAUSE
IRRITATION.
FIRST AID:
1. MOVE PERSON TO FRESH AIR
2. WASH WITH SOAP AND WATER
3. FLUSH EYES WITH WATER FOR AT LEAST
15 MINUTES AND CONTACT A PHYSICIAN

MATERIAL SAFETY DATA SHEET
For Coatings, Resins and Related Materials

01/28/05

*FR220
Fungicidal
Sealer*

SECTION I - PRODUCT IDENTIFICATION

Manufacturer: RICO CHEMICALS, INC.
P.O. BOX 1003
COLLIER ROAD
TUCUMCA

Information Phone: (404)-886-2189
Emergency Phone: (404)-886-2189

Product Class:
Trade Name : CLEAR BASE
Product Code : L-449
C.A.S. Number:

GA 30577 : Hazard Ratings: Health - 5
: none -> extreme Fire - 3
: 0 -> 4 Reactivity - 0

SECTION II - HAZARDOUS INGREDIENTS

Ingredients	CAS #	Weight %	Exposure Limits	Vapor Pr. mm Hg
XYLENE	1330-20-7	5-20	100. ppm	9.5
ISOBUTYL ACRYLATE	108-21-4	5-20	150. ppm	12.5
GLYCOL ETHER ESTER	111-15-9	5-20	5. ppm	6.
TOLUENE	108-88-3	1-5	200. ppm	38.
ACETONE	67-64-1	20-50	1000. ppm	150.

SECTION III - PHYSICAL DATA

Boiling Range: 132 - 204 Deg. F
Flash Point: 3.05 x n-Butyl Acetate
Relative Volatile: 22.7 %
Appearance: CLEAR LIQUID

Vapor Density: Heavier than Air.
Liquid Density: Lighter than Water.
Wgt per gallon: 7.2 Pounds.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Class: Flash Point: ~ F sec LEL : 1.

-EXTINGUISHING MEDIA:
FOAM, CARBON DIOXIDE OR DRY CHEMICAL.

-SPECIAL FIREFIGHTING PROCEDURES:
WATER SPRAY MAY BE INEFFECTIVE. WATER SHOULD BE USED TO COOL CONTAINERS.

-UNUSUAL FIRE & EXPLOSION HAZARDS:
KEEP MATERIAL FROM HEAT, SPARKS AND OPEN FLAMES.

SECTION V - HEALTH HAZARD DATA

-PERMISSIBLE EXPOSURE LEVEL:

-EFFECTS OF OVEREXPOSURE:
INHALATION: HEADACHE, NAUSEA OR IMPAIRED REACTION TIME AND COORDINATION
SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

-FIRST AID:
INHALATION: MOVE PERSON TO FRESH AIR
SKIN CONTACT: WASH WITH SOAP AND WATER
EYE CONTACT: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES AND CONTACT A PHYSICIAN