

MATERIAL SAFETY DATA SHEET
 FOR COATINGS, RESINS AND RELATED MATERIALS
 (Approved by U.S. Department of Labor. "Essentially Similar" to Form OSHA 20)

WASCO

MANUFACTURING, INC.

1306 West Spring Street □ P.O. Box 987 □ Monroe, Georgia 30655 □ (800) 334-8012

Page 1 of 3

Polytranspar Lacquer-Based Airbrush Paint FP10 through FP445

Section I -- Product Identification

Date of Prep: 06/30/93

Manufacturer's Name: WASCO Manufacturing, Inc.
 Street Address: 1306 West Spring Street
 City, State, Zip: Monroe, GA 30655

Emergency Telephone Number: (800) 334-8012

Manufacturer's Code Number: FP10 through FP445

Trade Name: Polytranspar Polymer-Lacquer
 Airbrush Paint

Section II -- Hazardous Ingredients

Ingredients	CAS#	Weight %	Exposure Limits	Vapor Pr mm Hg
XYLENE	1330-20-7	5-20	100. ppm	9.5
ISOBUTYL ACETATE	108-21-4	5-20	150. ppm	12.5
GLYCOL ETHER ESTER	111-15-9	5-20	5. ppm	6.
TOLUENE	108-88-3	1-5	200. ppm	38.
ACETONE	67-64-1	20-50	1000. ppm	180.
2-BUTOXYETHANOL	111-76-2	1-5	25. ppm	.6

Section III -- Physical Data

Boiling Range: 132 - 378 degrees F

Vapor Density: Heavier than air

Liquid Density: Lighter than water

Evaporation Rate: 3.66 x n-Butyl Acetate

Percent Volatile by Volume: 91.8%

Weight per Gallon: 7.35 lbs.

Appearance: Clear or Colored Liquid Paint

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by U.S. Department of Labor. "Essentially Similar" to Form OSHA 20)

WASCO

MANUFACTURING, INC.

1306 West Spring Street □ P.O. Box 967 □ Monroe, Georgia 30655 □ (800) 334-8012

Page 2 of 3

Polytranspar Lacquer-Based Airbrush Paint FP10 through FP445

Section IV -- Fire and Explosion Hazard Data

Flash Point: -4 degrees F (tcc)
Lel: 1
Extinguishing Media: Foam, CO2, Dry Chemical
Special Firefighting Procedures: Water spray may be ineffective. Water should be used to cool containers.
Unusual Fire and Explosion Hazards: Keep material away from heat, sparks and open flames.

Section V -- Health Hazard Data

Effects of Overexposure:

INHALATION: Headache, nausea or impairment of reaction time or coordination.
SKIN CONTACT: Prolonged or repeated contact may cause irritation.

Emergency and First Aid Procedures:

INHALATION: Move person to fresh air.
SKIN CONTACT: Wash affected areas with soap and water.
EYE CONTACT: Flush eyes with water for at least 15 minutes and consult a physician.

Section VI -- Reactivity Data

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: NA
Conditions to Avoid: Keep material from heat, sparks and open flames.
Hazardous Decomposition Products: NA

Section VII -- Spill or Leak Procedures

Steps to be taken in case material is released or spilled:

Remove all sources of ignition and ventilate vapors. Absorb with an inert material.

Waste Disposal Method:

Absorb, recycle or dispose of in accordance with local, state, and federal regulations.

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by U.S. Department of Labor. "Essentially Similar" to Form OSHA 20)

WASCO

MANUFACTURING, INC.

1306 West Spring Street □ P.O. Box 907 □ Monroe, Georgia 30655 □ (800) 334-8012

Page 3 of 3

Polytranspar Lacquer-Based Airbrush Paint FP10 through FP445

Section VIII -- Special Protective Information

Respiratory Protection: Adequate ventilation is required. In confined areas, use a NIOSH approved respirator.
Ventilation: Provide sufficient ventilation to keep vapor concentration below given "TVL" and "Lel".

Section VIII -- Special Protective Information (continued)

Protective gloves: Required for prolonged or repeated contact.
Eye Protection: Use eye protection adequate to prevent any contact of material with eyes.
Other Protective Equipment: None

Section IX -- Special Precautions

Precautions to be Taken in Handling and Storage:
Keep material away from heat, sparks or open flames. Close containers after each use.
Other Precautions:
When transferring or handling this material, use proper grounding and bonding procedures.

This product Safety Data Sheet is offered solely for your information, consideration and investigation. WASCO Manufacturing Inc. provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of data contained herein. WASCO Manufacturing Inc. urges persons receiving this information to make their own determination as to the information suitability for their particular application.

Section VIII -- Special Protective Information

Respiratory Protection:	NIOSH approved respirator
Ventilation:	As needed
Protective gloves:	Prolonged or repeated contact
Eye Protection:	Safety eye wear
Other Protective Equipment:	None

Section IX -- Special Precautions

Precautions to be Taken in Handling and Storage:
Keep away from heat, sparks or open flames.

Other Precautions:
Bond and ground when transferring materials.