

6-22-1995 8:21PM FROM

P. 2

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME:
 CHEM Oddities, Inc.
 P.O. Box 5125
 St. Louis, MO 63139

EMERGENCY TELEPHONE NUMBER:
 314-843-2523

INFORMATION TELEPHONE NUMBER:
 314-843-2523

DATE OF PREPARATION:
 January 1, 2004

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER: ORIGINAL CREATIONS, ALL COLORS
 PRODUCT NAME: LIFETONE
 PRODUCT CLASS: ~~PERFUME~~

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	WEIGHT PERCENT	OCCUPATIONAL EXPOSURE LIMITS	VAPOR PRESSURE mm Hg @ TEMP
DIACETONE	123-42-2	<5	50 ppm PEL	0.8 @ 20°C
ISOPROPANOL	67-63-0	15	400 ppm PEL	30.0 @ 20°C
METHYL ETHYL KETONE	78-93-3	10	200 ppm OSHA	82.5 @ 20°C
BUTYL ACETATE	123-86-4	25	150 ppm TWA	10.0 @ 20°C
BUTYL ALCOHOL	71-36-3	10	100 ppm TWA PEL	5.5 @ 20°C
ALIPHATIC HYDROCARBONS	64742-95-6	<5	100 ppm PEL	3.0 @ 20°C
TOLUENE	000108883	15	100 ppm (skin), 200 PEL	22.7 @ 20°C
XYLENE	1330-20-7	20	100 ppm PEL	9.5 @ 20°C

SECTION III - PHYSICAL DATA

BOILING RANGE: 174 °F VAPOR DENSITY: Heavier than air
 EVAPORATION RATE: Slower than ether % VOLATILE by VOLUME: 88% WEIGHT/GAL: 7.6 lbs.

SECTION IV - FIRE AND EXPLOSION DATA

FLAMMABILITY CLASSIFICATION: FLAMMABLE LIQUID - CLASS IB
 FLASH POINT: 35 °F LEL: 1.0
 EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS:

DO NOT USE WATER. FLAMMABLE LIQUID CAN RELEASE VAPORS THAT FORM FLAMMABLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASHPOINT. ELIMINATE AND ISOLATE FROM ALL SOURCES OF IGNITION. COMBUSTION WILL PRODUCE CO2, CO, AND TOXIC GASES.

SPECIAL FIREFIGHTING PROCEDURES:

WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND WHEN FIGHTING FIRES. USE WATER FOG NOZZLES TO COOL CLOSED CONTAINERS.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

EYES - IRRITATING, MAY INJURE EYE TISSUE IF NOT PROPERLY REMOVED
 SKIN - SLIGHT IRRITATION DUE TO SOLVENTS
 INHALATION - IRRITATION TO RESPIRATORY TRACT, NOSE, THROAT, LUNGS
 INGESTION - CONSULT PHYSICIAN, DO NOT TAKE INTERNALLY
 MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:
 RESPIRATORY PROBLEMS CAN BE INCREASED BY INHALATION OF VAPORS.

6-29-1995 6:21PM FROM

P. 3

PRIMARY ROUTES OF ENTRY: DERMAL, INHALATION

EMERGENCY FIRST AID PROCEDURES:

YES - FLUSH WITH WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION.
SKIN - REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA WITH SOAP AND WATER.
INHALATION - MOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IF NEEDED.
INGESTION - DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

SECTION VI - REACTIVITY DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR