

MINWAX DIV OF EASTMAN KODAK -- MO60370 MINWAX FAST DRYING
POLYURETHANE
CLEAR-ALL - SATIN
MATERIAL SAFETY DATA SHEET
FSC: 9160
NIIN: 00F039162
Manufacturer's CAGE: 0K1A4
Part No. Indicator: A
Part Number/Trade Name: MO60370 MINWAX FAST DRYING POLYURETHANE
CLEAR-ALL
FINISHES

=====
=====
General Information
=====
=====

Item Name: SATIN
Company's Name: MINWAX CO DIV OF EASTMAN KODAK CO
Company's Street: 15 MERCEDES DRIVE
Company's P. O. Box: 438
Company's City: MONTVALE
Company's State: NJ
Company's Country: US
Company's Zip Code: 07645-5000
Company's Emerg Ph #: 201-391-0253/201-573-5700
Company's Info Ph #: 201-573-5700/201-391-0253
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SE
Date MSDS Prepared: 31OCT94
Safety Data Review Date: 06APR95
Preparer's Company: MINWAX CO DIV OF EASTMAN KODAK CO
Preparer's St Or P. O. Box: 15 MERCEDES DRIVE
Preparer's City: MONTVALE
Preparer's State: NJ
Preparer's Zip Code: 07645-5000
MSDS Serial Number: BWWKR

=====
=====
Ingredients/Identity Information
=====
=====

Proprietary: NO
Ingredient: MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-
NAPTHANES
MINERAL SPIRITS
Ingredient Sequence Number: 01
Percent: 20-26
NIOSH (RTECS) Number: 1003692SN
CAS Number: 64742-88-7
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM
Other Recommended Limit: 100 PPM

Proprietary: NO
Ingredient: STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL
SPIRITS
Ingredient Sequence Number: 02
Percent: 29-40
NIOSH (RTECS) Number: WJ8925000
CAS Number: 8052-41-3
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM
Other Recommended Limit: 525 MG/CUM

Proprietary: NO
Ingredient: VOLATILE ORGANIC COMPOUNDS: < 540 G/L
Ingredient Sequence Number: 03
NIOSH (RTECS) Number: 9999999VO

=====
=====

Physical/Chemical Characteristics

=====
=====

Appearance And Odor: CLEAR AMBER LIQUID W/HYDROCARBON ODOR
Specific Gravity: 0.871
Solubility In Water: INSOLUBLE

=====
=====

Fire and Explosion Hazard Data

=====
=====

Flash Point: >101F
Flash Point Method: SCC

Extinguishing Media: WATER SPRAY, FOAM, DRY CHEMICAL/CO2.
Special Fire Fighting Proc: DON'T USE A DIRECT STREAM OF WATER. WEAR SCBA & PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.
Unusual Fire And Expl Hazrds: COMBUSTIBLE. PRODUCT MAY FLOAT & CAN BE IGNITED ON SURFACE OF WATER. CONTAINERS EXPOSED TO INTENSE HEAT MAY RUPTURE.

=====
=====

Reactivity Data

=====
=====

Stability: YES
Cond To Avoid (Stability): HEAT, SPARKS, OPEN FLAME & OTHER SOURCES OF IGNITION.
Materials To Avoid: STRONG OXIDIZING AGENTS.
Hazardous Decomp Products: HYDROCARBON FUMES, SMOKE, CO.
Hazardous Poly Occur: NO

=====
=====

Health Hazard Data

=====
=====

Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NONE
Signs/Symptoms Of Overexp: IRRITATION.
Med Cond Aggravated By Exp: PRE-EXISTING LUNG DISORDERS
WASH THOROUGHLY W/SOAP & WATER. EYES: REMOVE CONTACT LENSES, FLUSH W/
PLENTY OF WATER. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION

IN ALL CASES.

=====

Precautions for Safe Handling and Use

=====

Steps If Matl Released/Spill: SMALLS: ABSORB W/SAND/OTHER SUITABLE
ABSORBENT MATERIAL & PLACE IN A CONTAINER FOR DISPOSAL. LARGE:
AREA MAY BE
SLIPPERY, DIKE AROUND W/ABSORBENT MATERIAL. TRANSFER LIQUIDS &
CONTAMINATED

DIKING MATERIAL TO SEPERATE CONTAINERS FOR RECOVERY/DISPOSAL.
Waste Disposal Method: DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS.

Precautions-Handling/Storing: DON'T USE/STORE NEAR HEAT, SPARKS, FLAME/
OTHER SOURCES OF IGNITION. CLOSE CONTAINER AFTER EACH USE.

Other Precautions: DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN/EYES.
KEEP

OUT OF REACH OF CHILDREN. AVOID INHALATION, USE ONLY
W/ADEQUATE
VENTILATION.

=====

Control Measures

=====

Respiratory Protection: WEAR NIOSH/MSHA/EQUIVALENT RESPIRATOR/LEAVE
AREA.

Ventilation: REQUIRED

Protective Gloves: RUBBER

Eye Protection: SAFETY GLASSES

=====

Transportation Data

=====

=====

Disposal Data

=====
=====

=====
=====

Label Data

=====
=====

Label Required: YES
Label Status: G
Common Name: MO60370 MINWAX FAST DRYING POLYURETHANE CLEAR-
ALL
FINISHES
Special Hazard Precautions: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL.
IRRITATION.
Label Name: MINWAX CO DIV OF EASTMAN KODAK CO
Label Street: 15 MERCEDES DRIVE
Label P.O. Box: 438
Label City: MONTVALE
Label State: NJ
Label Zip Code: 07645-5000
Label Country: US
Label Emergency Number: 201-391-0253/201-573-5700

=====
=====

URL for this msds <http://hazard.com>. If you wish to change, add to, or delete information in this archive please sent updates to dan@hazard.com.