

MINWAX (R) POLYSHADES (R) ALL SHADES & SHEENS (3 NEW SHADES)

The Thompson Minwax Company
MINWAX COMPANY Div.
P.O. Box 438
Montvale, NJ 07645

MINWAX (R) POLYSHADES (R) ALL SHADES & SHEENS (3 NEW SHADES)

SECTION #3 - PHYSICAL DATA Continued...

Pounds Per Gallon: 7.47 - 7.75

pH: Not applicable

Viscosity: 175 +/- 25 cps

VOC (g/l): 450 maximum

Appearance

Clear, slightly viscous liquid with characteristic color (see Section 1) and hydrocarbon odor.

TELEPHONE CONTACTS:
NON-MEDICAL, PRODUCT INFORMATION (DAY): 1-800-523-9299
TRANSPORTATION (DOT) EMERGENCIES ONLY (CHEMTREC): 1-800-424-9300
MEDICAL EMERGENCIES ONLY: 1-800-228-5635, EXTENSION 218

SECTION #1 - IDENTIFICATION

Product: MINWAX (R) POLYSHADES (R) ALL SHADES & SHEENS (3 NEW SHADES)

SHADE	GLOSS	SATIN	GLOSS FORMULA	SATIN FORMULA
Honey Pine	410	310	M060378	M060533
Pecan	420	320	M060379	M060534
Olde Maple	430	330	M060380	M060535
Antique Walnut	440	340	M060381	M060536
Royal Walnut	450	350	M060382	M060537
Tudor	460	360	M060383	M060538
Classic Oak	470	370	M060755	M060775
Bombay Mahogany	480	380	M060751	M060752
Natural Cherry	490	390	M060753	M060754

THIS MSDS APPLIES TO THE FOLLOWING:
Special Hazards: Danger: Harmful or fatal if swallowed. Skin irritant. Combustible.

HAZARD RATINGS:

NFPA - Health: 2 Moderate
Fire: 2 Moderate
Reactivity: 0 Negligible
HMIS - Health: 2 Moderate
Flammability: 2 Moderate
Reactivity: 0 Minimal

Product Description: Wood stain and polyurethane topcoat in one-step.

SECTION #2 - HAZARDOUS CHEMICAL COMPONENTS

Component: DISTILLATES (PETROLEUM), HYDROTREATED LIGHT
CAS Number: 64742-47-8
Percent of Mixture: 27.0 to 33.0
RECOMMEND USE OF EXPOSURE LIMITS FOR STODDARD SOLVENT:
ACGIH TLV-TWA: 100 ppm
OSHA PEL-TWA: 500 ppm

Component: SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC
CAS Number: 64742-88-7
Percent of Mixture: 14.0 to 19.0
RECOMMEND USE OF EXPOSURE LIMITS FOR STODDARD SOLVENT:
ACGIH TLV-TWA: 100 ppm
OSHA PEL-TWA: 500 ppm

Component: STODDARD SOLVENT
CAS Number: 8052-41-3
ACGIH TLV-TWA: 100 ppm
Percent of Mixture: 0 to 1.5
OSHA PEL-TWA: 500 ppm

SECTION #3 - PHYSICAL DATA

Vapor Pressure: Not Determined
Vapor Density (Air=1): Not Determined
Specific Gravity: 0.895±.029
Solubility (H2O): Insoluble

I.D.#: 101402

POLYSHADES, HONEY PINE, QT.#310

VENDOR: RIGHT-WAY DEALER WAREHOUSE

VENDOR PART#: 61310

eye contact, flush with plenty of water. Call physician.

SECTION #4 - FIRE FIGHTING & EXPLOSION DATA

Flash Point: >101°F SETA

Lower Explosive Limit (%): Not Determined
Upper Explosive Limit (%): Not Determined

Fire and Explosion Hazards

DANGER: Contains mineral spirits. Combustible. Do not use or store near heat, sparks, flame or other sources of ignition. Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure build-up which could result in container rupture.

Extinguishing Media

Water spray, foam, dry chemical or carbon dioxide. Do not use a direct stream of water. Product may float and may be reignited on surface of water.

Special Fire Fighting Instructions

Wear self-contained breathing apparatus and protective clothing appropriate for fighting a typical chemical fire. Use water spray to cool fire-exposed containers.

SECTION #5 - EXPOSURE EFFECTS and FIRST AID

Route of Exposure - Inhalation

Avoid inhalation and use only with adequate ventilation.

First Aid - Inhalation

If affected by inhalation, remove to fresh air. Get medical attention if needed.

Route of Exposure - Skin

Skin irritant. Avoid contact with skin. Wear rubber gloves when handling.

First Aid - Skin

Wash thoroughly with soap and water. If irritation persists, get medical attention.

Route of Exposure - Eyes

Avoid contact with eyes.

First Aid - Eyes

SECTION #5 - EXPOSURE EFFECTS and FIRST AID Continued...

Route of Exposure - Ingestion

Harmful or fatal if swallowed. Do not take internally. Contains mineral spirits.

First Aid - Ingestion

If swallowed, do not induce vomiting. Call physician immediately.

Miscellaneous Toxicological Information

Carcinogenicity: NTP: NO IARC: NO OSHA: NO

SECTION #6 - REACTIVITY & POLYMERIZATION

Stability: Stable.

Conditions to Avoid (Stability)

Heat, sparks, open flame, all sources of heat or ignition.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Hydrocarbon fumes, smoke, carbon monoxide (where combustion is incomplete) may be formed during thermal decomposition.

Hazardous Polymerization: Will not occur.

SECTION #7 - SPILL, LEAK, & DISPOSAL PROCEDURES

Steps to be Taken in The Event of Spills, Leaks, or Release

Absorb small spills with sand or other suitable absorbent material and place in a container for disposal. For large spills, area may be slippery, dike around spill with absorbent material. Transfer liquids and contaminated diking material to separate, suitable containers for recovery or disposal.

Waste Disposal Methods

Dispose of in accordance with local, state, and federal regulations.

Other Environmental Information

None of the ingredients in this product meet the reporting requirements of the SARA Title III, Section 313 List of Toxic Chemicals.

SECTION #8 - SPECIAL PROTECTIVE MEASURES

Ventilation

Use only with adequate ventilation. If using indoors, open all windows and doors to make sure there is fresh air movement.

Eye Protection

Avoid contact with eyes. Wear safety glasses when handling.

Skin Protection

Wear rubber gloves when handling.

SECTION #8 - SPECIAL PROTECTIVE MEASURES Continued...

Respiratory Protection

Avoid inhalation.

SECTION #9 - SPECIAL PRECAUTIONS - STORAGE & HANDLING

Storage & Handling Conditions

DANGER: Contains mineral spirits. Harmful or fatal if swallowed. Do not take internally. Skin irritant. Avoid contact with skin and eyes. Wear rubber gloves and safety glasses when handling. Use only with adequate ventilation and avoid inhalation. If using indoors, open all windows and doors to make sure there is fresh air movement. Do not use or store near heat, sparks, flame, or other sources of ignition. KEEP OUT OF REACH OF CHILDREN.

SECTION #11 - OTHER INFORMATION

NEW JERSEY WORKER AND COMMUNITY RIGHT TO KNOW ACT:
The following information is provided to assist employers in the state of New Jersey to label products in the workplace in accordance with the Worker and Community Right to Know Act (N.J.A.C. 8:59)

Ingredient

CAS#

SOYA OIL URETHANE ALKYD RESIN	68188-21-6
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC	64742-88-7
AMORPHOUS SILICA	112926-00-8
DICHLORODIMETHYL SILANE (reaction product with silica)	68611-44-9
STODDARD SOLVENT	8052-41-3

STATE REGULATED COMPONENTS

Component: STODDARD SOLVENT
CAS Number: 8052-41-3

State Regulations: ILL MAS NJW PAW
Percent of Mixture: 0 to 1.5

ILL - Illinois Toxic Substance
MAS - Massachusetts Hazardous Substance
NJE - New Jersey Environmental Hazardous Substance
NJS - New Jersey Special Health Hazardous Substance
NJW - New Jersey Workplace Hazardous Substance
PAE - Pennsylvania Environmental Hazardous Substance
PAS - Pennsylvania Special Hazardous Substance
PAW - Pennsylvania Workplace Hazardous Substance
P65 - California Proposition 65