

OHIO STATE UNIVERSITY COLLEGE OF BIOLOGICAL SCIENCES MSDS FILE

MINWAX DIV OF EASTMAN KODAK -- MO60370 MINWAX FAST DRYING
POLYURETHANE

CLEAR-ALL - SATIN

MATERIAL SAFETY DATA SHEET

FSC: 9160

NIIN: 00F039162

Manufacturer's CAGE: 0K1A4

Part No. Indicator: A

Part Number/Trade Name: MO60370 MINWAX FAST DRYING POLYURETHANE
CLEAR-ALL

FINISHES

=====
=====

General Information

=====
=====

Item Name: SATIN

Company's Name: MINWAX CO DIV OF EASTMAN KODAK CO

Company's Street: 15 MERCEDES DRIVE

Company's P. O. Box: 438

Company's City: MONTVALE

Company's State: NJ

Company's Country: US

Company's Zip Code: 07645-5000

Company's Emerg Ph #: 201-391-0253/201-573-5700

Company's Info Ph #: 201-573-5700/201-391-0253

Record No. For Safety Entry: 001

Tot Safety Entries This Stk#: 001

Status: SE

Date MSDS Prepared: 31OCT94

Safety Data Review Date: 06APR95

Preparer's Company: MINWAX CO DIV OF EASTMAN KODAK CO

Preparer's St Or P. O. Box: 15 MERCEDES DRIVE

Preparer's City: MONTVALE

Preparer's State: NJ

Preparer's Zip Code: 07645-5000

MSDS Serial Number: BWWKR

=====
=====

Ingredients/Identity Information

Proprietary: NO
Ingredient: MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-
NAPHTHANES
MINERAL SPIRITS
Ingredient Sequence Number: 01
Percent: 20-26
NIOSH (RTECS) Number: 1003692SN
CAS Number: 64742-88-7
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM
Other Recommended Limit: 100 PPM

Proprietary: NO
Ingredient: STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL
SPIRITS
Ingredient Sequence Number: 02
Percent: 29-40
NIOSH (RTECS) Number: WJ8925000
CAS Number: 8052-41-3
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM
Other Recommended Limit: 525 MG/CUM

Proprietary: NO
Ingredient: VOLATILE ORGANIC COMPOUNDS: < 540 G/L
Ingredient Sequence Number: 03
NIOSH (RTECS) Number: 9999999VO

Physical/Chemical Characteristics

Appearance And Odor: CLEAR AMBER LIQUID W/HYDROCARBON ODOR
Specific Gravity: 0.871
Solubility In Water: INSOLUBLE

Fire and Explosion Hazard Data

Flash Point: >101F
Flash Point Method: SCC
Extinguishing Media: WATER SPRAY, FOAM, DRY CHEMICAL/CO2.
Special Fire Fighting Proc: DON'T USE A DIRECT STREAM OF WATER. WEAR SCBA & PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.
Unusual Fire And Expl Hazrds: COMBUSTIBLE. PRODUCT MAY FLOAT & CAN BE IGNITED ON SURFACE OF WATER. CONTAINERS EXPOSED TO INTENSE HEAT MAY RUPTURE.

Reactivity Data

Stability: YES
Cond To Avoid (Stability): HEAT, SPARKS, OPEN FLAME & OTHER SOURCES OF IGNITION.
Materials To Avoid: STRONG OXIDIZING AGENTS.
Hazardous Decomp Products: HYDROCARBON FUMES, SMOKE, CO.
Hazardous Poly Occur: NO

Health Hazard Data

Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NONE
Signs/Symptoms Of Overexp: IRRITATION.
Med Cond Aggravated By Exp: PRE-EXISTING LUNG DISORDERS

WASH THOROUGHLY W/SOAP & WATER. EYES: REMOVE CONTACT LENSES, FLUSH W/ PLENTY OF WATER. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION

IN ALL CASES.

=====

Precautions for Safe Handling and Use

=====

Steps If Matl Released/Spill: SMALLS: ABSORB W/SAND/OTHER SUITABLE ABSORBENT MATERIAL & PLACE IN A CONTAINER FOR DISPOSAL. LARGE: AREA MAY BE SLIPPERY, DIKE AROUND W/ABSORBENT MATERIAL. TRANSFER LIQUIDS & CONTAMINATED

DIKING MATERIAL TO SEPERATE CONTAINERS FOR RECOVERY/DISPOSAL. Waste Disposal Method: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Precautions-Handling/Storing: DON'T USE/STORE NEAR HEAT, SPARKS, FLAME/ OTHER SOURCES OF IGNITION. CLOSE CONTAINER AFTER EACH USE.

Other Precautions: DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN/EYES. KEEP

OUT OF REACH OF CHILDREN. AVOID INHALATION, USE ONLY W/ADEQUATE VENTILATION.

=====

Control Measures

=====

Respiratory Protection: WEAR NIOSH/MSHA/EQUIVALENT RESPIRATOR/LEAVE AREA.

Ventilation: REQUIRED

Protective Gloves: RUBBER

Eye Protection: SAFETY GLASSES

=====

Transportation Data

=====
=====
=====
=====

Disposal Data

=====
=====
=====
=====

Label Data

=====
=====

Label Required: YES
Label Status: G
Common Name: MO60370 MINWAX FAST DRYING POLYURETHANE CLEAR-
ALL
FINISHES
Special Hazard Precautions: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL.
IRRITATION.
Label Name: MINWAX CO DIV OF EASTMAN KODAK CO
Label Street: 15 MERCEDES DRIVE
Label P.O. Box: 438
Label City: MONTVALE
Label State: NJ
Label Zip Code: 07645-5000
Label Country: US
Label Emergency Number: 201-391-0253/201-573-5700

=====
=====

URL for this msds <http://hazard.com>. If you wish to change, add to, or delete information in this archive please sent updates to dan@hazard.com.