

2400, 2401, 2405, 2408, 2409, 2410, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2423, 2424, 2425, 2428, 2429, 2430, 2431, 2432, 2448, 2450, 2455, 2480, 2481, 2490, 2494, 2499

MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION:
 MANUFACTURER'S NAME:
 MANUFACTURER'S ADDRESS:

SECTION I: PRODUCT INFORMATION

PRODUCT NAME: Goof Off, Non-Aerosol
 MANUFACTURERS CODE IDENTIFICATION: 2400, 2401, 2405, 2408, 2409, 2410, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2423, 2424, 2425, 2428, 2429, 2430, 2431, 2432, 2448, 2450, 2455, 2480, 2481, 2490, 2494, 2499
 PRODUCT CLASS: Liquid Cleaner

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	CAS Number	%	BY WGT.	Occupational Exposure Limits			Vapor Pres.
				PEL	TLV	UNITS	LEL
Xylene	1330-20-7	90 - 95		100	100	ppm	1.00
+ Diethylene glycol monomethyl ether	111-77-3	1 - 5		---	---	---	ND

+ SARA III - Section 313 Toxic Chemical

SECTION III: PHYSICAL DATA

EVAPORATION RATE: FASTER SLOWER THAN ETHER
 VAPOR DENSITY: HEAVIER LIGHTER THAN AIR
 BOILING RANGE: 147°F Initial Boiling Point C.A.R.B. VOC:
 PERCENT VOLATILE: 99 POUNDS PER GALLON: 7.3 SPECIFIC GRAVITY .87 typical

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASS: IB Flammable Liquid
 LOWER EXPLOSIVE LIMIT: See Section II
 HMIS RATING:
 Health 2 Flammability 3 Reactivity 0
 FLASH POINT: 50°F
 EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide. Water is not suitable as an extinguishing media, but may be used to cool nearby containers.

2400, 2401, 2405, 2408, 2409, 2410, 2414, 2415, 2416, 2417, 2418, 2419, 2420, 2423, 2424, 2425, 2428, 2429, 2430, 2431, 2432, 2448, 2450, 2455, 2480, 2481, 2490, 2494, 2499

2400

VENTILATION: Control airborne concentrations below exposure guidelines. Local exhaust ventilation may be necessary.

PROTECTIVE GLOVES: Use chemical resistant gloves when necessary to protect from personal exposure.

EYE PROTECTION: Face shield or safety glasses are recommended.

OTHER PROTECTIVE EQUIPMENT: Other protective clothing should be used as necessary to protect from personal exposure. Ground all containers when transferring material.

SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers closed when not in use. Do not use or store near open flame or strong oxidizers.

OTHER PRECAUTIONS: Avoid breathing vapors or spray mists. Avoid prolonged or repeated personal contact. Wash thoroughly after use.

DOT INFORMATION

UN Number	UN1307
Classification	3
Proper Shipping Name	Xylene solution
Packing Group	II
Exceptions	49CFR §173.150(b) & (c) allow for the use of the "ORM-D Consumer Commodity" classification for domestic ground shipment of packages <0.3 gallons net each.

KEEP OUT OF REACH OF CHILDREN

Creation Date: 04-28-97
Revision Date: 16MAY00
Revision Number: 4.0