

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-348-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 83H SUPER 300 FORM- A- GASKET SEALANT .25PT
Item No: 80057
Product Type: Sealant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
2-PROPANOL 67-63-0	35-45	400 ppm TWA; 983 mg/m ³ TWA	400 ppm TWA
VEGETABLE OIL 68187-84-8	20-30	Not Listed	Not Listed
ROSIN 8050-09-7	10-20	sensitizer; reduce exposure to as low as possible	15 mg/m ³ total dust; 5 mg/m ³ respir.
TALC 14807-96-6	5-15	2 mg/m ³ respir. dust TWA	2 mg/m ³ TWA
POLYVINYL RESIN 63148-65-2	1-10	Not Listed	Not Listed
CARBON BLACK 1333-86-4	0.1-1.0	3.5 mg/m ³	3.5 mg/m ³ TWA

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Oral LD50 greater than 5000 mg/kg.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.
Signs and Symptoms of Exposure: Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Overexposure may cause eye and skin redness.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
CARBON BLACK 1333-86-4	0.1-1.0		Group A4	Group 2B; Vol. 65, pg 149, 1996

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention..
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): 76 degrees F. Method: Tag Closed Cup
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products Formed by Fire or Thermal Decomposition: Aldehydes, Oxides of carbon. Carboxylic acids
Unusual Fire/Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat.
Lower Explosive Limit: 2

Upper Explosive Limit:

12

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Residues may be cleaned up with isopropyl alcohol.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

Handling: Avoid contact with skin and eyes. Do not inhale vapors. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses or goggles.

Skin: Rubber or plastic gloves

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits during the use of this product.

Respiratory Protection: An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black paste

Odor: Alcohol Odor

Boiling Point (°F): 180 degrees F.

pH: Does not apply

Solubility in Water: Partial

Specific Gravity: 1.0

VOC Content(Wt.%): 38.7% by weight

Vapor Pressure: 33 mm Hg @ 68 degrees F.

Vapor Density (Air=1): 2.07

Evaporation Rate: 7.7 (ether = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: WILL NOT OCCUR

Incompatibilities: Strong oxidizers.

Conditions to Avoid: Do not expose to heat or store at temperatures above 120 F.

Hazardous Products Formed by Fire or Thermal Decomposition: Aldehydes, Oxides of carbon. Carboxylic acids

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Consumer Commodity (Not more than five liters)

Hazard Class: ORM-D

UN/ID Number: None

Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 500 ml)

Class or Division: Class 9

UN/NA Number: ID 8000

Product name: 83H SUPER 300 FORM- A- GASKET
SEALANT .25PT

Item 80057

IMDG

Proper Shipping: Resin Solution, Flammable, Limited Quantity
Hazard Class: Class 3.3
UN Number: UN 1866

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: **YES** All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 0

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA
06106

Revision Date: 03/03/2004

Revision 2

Number:

Telephone Number: 1-87-Permatex (877) 376-2839