

M A T E R I A L S A F E T Y D A T A S H E E T

7545

TASKI ULTRA					
PRODUCT INFORMATION					
Product Type:	Floor Finish Latex	Emergency Phone Number: 1-800-228-5635, ext. 072			
Supplied By:	Lever Industrial Inc. 1151 Green Valley Road London, Ontario N6A 4C2 (519) 668-6211	Distributed By:	Lever Industrial Co., 7450 Industry Drive, North Charleston, SC 29418-8431 1-800-827-5487		
PREPARATION INFORMATION					
Prepared On:	08/22/91	Supersedes: 06/18/91			
Prepared By:	Technical Department, Lever Industrial Inc.	The information here is presented in good faith, but no warranty, warranty, expressed or implied is given.			
References:	NAV = Not Available	NAP = Not Applicable	DOT = Department of Transportation		
HAZARDOUS INGREDIENTS					
Ingredient	CAS #	% Optional	OSHA:PEL	OSHA:STEL	ACGIH:TWA
Diethylene Glycol Monoethyl Ether	111-90-0		NAV	NAV	NAV
Dipropylene Glycol Mono Methyl Ether	34590-94-8		100 ppm	150 ppm	100 ppm
PHYSICAL DATA					
Physical State:	Liquid	Specific Gravity:	1.023 - 1.033		
Vapour Pressure:	NAV	Coeff. of Water/Oil Dist.:	NAV		
Vapour Density:	NAV	Evaporation Rate:	> 1		
Boiling Point:	212°F (100°C)	Freezing Point:	NAV		
pH:	8.2 - 9.2	Solubility in Water:	Dispersible		
Appearance & Odour:	Milky white liquid, characteristic odour.				
FIRE & EXPLOSION HAZARD DATA					
Flash Point (TCC):	200°F (93°C)	Upper Explosion Limit:	NAP		
Lower Explosion Limit:	NAP	Hazardous Combustion Products:	Carbon dioxide, carbon monoxide		
Exinction Media:	Fog, CO2, dry chemical, foam				
Conditions to Avoid:	NAV				
Special Fire Fighting Procedures:	Do not enter confined spaces without protective clothing and self-contained breathing apparatus.				
Unusual Fire and Explosion Hazards:	None				
TOXICOLOGICAL PROPERTIES					
Route of Entry:	Eye contact, ingestion.				
Effects of Acute Exposure:	Mild eye irritant. Ingestion may cause nausea, abdominal discomfort, vomiting and diarrhea and mucousal irritation.				
Effects of Chronic Exposure:	Prolonged and repeated exposure may causes skin irritation. Ingestion of large amounts may cause kidney damage.				
Carcinogenicity:					
NTP?:	No				
IARC Monographs?:	No				
OSHA Regulated?:	No				
Signs and Symptoms of Exposure:					
Eyes:	Causes irritation				
Skin:	Prolonged and repeated exposure may causes irritation.				
Ingestion:	Causes gastro-intestinal irritation, nausea, vomiting, and diarrhea.				
Medical Conditions Generally Aggravated by Exposure:	NAV				

Lever Industrial

FIRST AID MEASURES

Eye Contact: Flush eyes with water for at least 15 minutes and call a physician immediately.

Skin Contact: Wash affected areas with large amounts of soap and water. If irritation persists, call a physician.

Ingestion: Do not induce vomiting. Dilute by drinking water. Call a physician immediately.

Inhalation: Move person to fresh air. Start artificial respiration if necessary. Oxygen may be administered. Call a physician.

PREVENTIVE MEASURES

Engineering Controls: General ventilation should be adequate.

Protective Equipment:

- Respiratory: Dust Mist respirator, if necessary
- Eye: For precaution use safety goggles
- Gloves: Impervious, Rubber, Neoprene, Plastic, if necessary
- Footwear: Boots, if necessary
- Clothing: Apron, coveralls, if necessary
- Other: Eye wash fountains and safety showers are recommended

Handling Procedures: Avoid ingestion and inhalation. Wear appropriate protective equipment to avoid eye and skin contact. Avoid generating airborne mists.

Storage Requirements: Keep from freezing. Failure to follow precaution could lead to product failure.

Leak and Spill Procedure: Safely stop spill at source. Contain spill with soil or other inert material. Mop, pump or absorb with material and reclaim into sound containers for proper disposal.

Waste Disposal: Dispose of in an approved waste facility according to Federal, State and local regulations.

REACTIVITY DATA

Conditions of Instability: Stable

Incompatible Materials: Salt solutions or acids will coagulate latex.

Conditions of Reactivity: NAV

Hazardous Decomposition Products: Burning may produce carbon monoxide, carbon dioxide and unidentified organic compounds.

SPECIAL SHIPPING INFORMATION

<u>DOT</u>	<u>DOT Shipping Name</u>	<u>DOT Hazard Class</u>	<u>DOT Label</u>	<u>Identification #</u>
No	NAP	NAP	NAP	NAP

TASKI ULTRA



Lever Industrial