

continued on page 3

skin exposure.

Respiratory and irritation or skin irritation may increase due to excessive
SIGNS AND SYMPTOMS OF OVEREXPOSURE
adverse effects to the user, usually and good respiratory hygiene.

Prolonged overexposure to volatile ingredients in section 3 may cause
nausea or dizziness.

In a confined area workers in rapid concentration may cause headache.

IRRITATION: Irritation of the upper respiratory system.

SKIN: Prolonged or repeated exposure may cause irritation.

EYES: Irritation.

EFFECTS OF OVEREXPOSURE

EYE OR SKIN CONTACT WITH THE PRODUCT: Avoid or spray water.

IRRITATION OF LABOR OR SPRAY WATER.

NOTES OF EXPOSURE

Section 3 -- HAZARD IDENTIFICATION

| | | | | |
|---|-----------|-------------------|---------------|----------|
| | | OSHA PEL | 32 ppm | |
| | | ACGIH TWA | 50 ppm | 0.88 ppm |
| S | 111-10-3 | 3-Bromobenzene | | |
| | | OSHA PEL | not available | |
| | | ACGIH TWA | not available | 0.1 ppm |
| S | 8-15-14-8 | Hydrochloric acid | | |
| | | OSHA PEL | not available | |
| | | ACGIH TWA | not available | 1 ppm |
| S | 8-15-14-8 | Hydrochloric acid | | |

| | | | | | | |
|---|----|----|---------|------------|------|---------------|
| 8 | PL | ML | CAS NO. | INGREDIENT | UNIT | WORK PRACTICE |
|---|----|----|---------|------------|------|---------------|

Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS

(800) 434-2300
Transportation Emergency
(312) 266-3871
Medical Emergency
(312) 266-3803
Respiratory Information
TELEPHONE NUMBERS AND WEBSITES
www.battledose.com

Office Branch, MS 38024
10130 Madison Blvd
THE THOMPSON, S COMPANY
MANUFACTURER'S NAME

THOMPSON, S DESCRIBED IN Label Market Brochure for Wood, Stain & Redwood
PRODUCT NAME

| | | | |
|----------------|---------------------|----------------|---|
| 1987 | 03-01-01 | Respiratory | 0 |
| | | Eye/Irritation | 0 |
| | | Health | 3 |
| PRODUCT NUMBER | DATE OF PREPARATION | HMIS CODES | |

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

00 00
1987

MATERIAL SAFETY DATA SHEET

MATERIAL SAFETY DATA SHEET

74841
08 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

| PRODUCT NUMBER | DATE OF PREPARATION | HMIS CODES |
|----------------|---------------------|--|
| 74841 | 02-OCT-07 | Health 2 Flammability 0 Reactivity 0 |

PRODUCT NAME

THOMPSON'S® DeckShield™ Tinted Waterproofer for Wood, Classic Redwood

MANUFACTURER'S NAME

THE THOMPSON'S COMPANY
10136 Magnolia Drive
Olive Branch, MS 38654

TELEPHONE NUMBERS and WEBSITES

Regulatory Information

(216) 566-2902

www.paintdocs.com

Medical Emergency

(216) 566-2917

Transportation Emergency

(800) 424-9300

for Chemical Emergency ONLY (spill, leak,
fire, exposure, or accident)

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

| % by WT | CAS No. | INGREDIENT | UNITS | VAPOR PRESSURE |
|---------|------------|--------------------------------------|---------------|----------------|
| 2 | 64742-48-9 | Hydrotreated Heavy Petroleum Naphtha | | |
| | | ACGIH TLV | Not Available | 1 mm |
| | | OSHA PEL | Not Available | |
| 2 | 64742-47-8 | Light Aliphatic Hydrocarbon | | |
| | | ACGIH TLV | Not Available | 0.1 mm |
| | | OSHA PEL | Not Available | |
| 2 | 111-76-2 | 2-Butoxyethanol | | |
| | | ACGIH TLV | 20 ppr | 0.88 mm |
| | | OSHA PEL | 25 ppr | |

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary and blood forming systems.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

Continued on page 2

74841

page 2

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATIONFor complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.

INGESTION: Do not induce vomiting.
Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

| | | |
|--------------------|------------|------------|
| FLASH POINT | LEL | UEL |
| Not Applicable | N.A. | N.A. |

FLAMMABILITY CLASSIFICATION

Not Applicable

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLEDRemove all sources of ignition. Ventilate the area.
Remove with inert absorbent.

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGEKeep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Continued on page 3

74841

page 3

 Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|----------------------------|---------------------------------|--|
| PRODUCT WEIGHT | 8.96 lb/gal | 1073 g/l |
| SPECIFIC GRAVITY | 1.08 | |
| BOILING POINT | 212 - 528 F | 100 - 275 C |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 75 % | |
| EVAPORATION RATE | Slower than ether | |
| VAPOR DENSITY | Heavier than air | |
| SOLUBILITY IN WATER | N.A. | |
| pH | 9.5 | |
| VOLATILE ORGANIC COMPOUNDS | (VOC Theoretical - As Packaged) | |
| 2.02 lb/gal | 242 g/l | Less Water and Federally Exempt Solvents |
| 0.70 lb/gal | 84 g/l | Emitted VOC |

Continued on page 4

74841

page 4

 Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

 Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

TOXICOLOGY DATA

| CAS No. | Ingredient Name | | | | |
|------------|------------------------------------|------|-----|-----|---------------|
| 64742-48-9 | Hydrotreated Heavy Petroleum Napht | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| | | | | | |
| 64742-47-8 | Light Aliphatic Hydrocarbon | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| | | | | | |
| 111-76-2 | 2-Butoxyethanol | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | 470 mg/kg |
| | | | | | |

 Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

 Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Continued on page 5

74841

page 5

 Section 14 -- TRANSPORT INFORMATION

US Ground (DOT)

Not Regulated for Transportation.

Canada (IDG)

Not Regulated for Transportation.

IMO

Not Regulated for Transportation.

 Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|---------|-------------------|---------|-----------|
| | Glycol Ethers | 2 | |

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

 Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.