

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U. S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB no. 1218-0072

0679502229
ML1-46

IDENTITY (As used on Label and List)
West Creek Pan Release

Note: Blank spaces are not permitted. If any item is not applicable, or no information available, THE SPACE MUST BE MARKED TO INDICATE THAT.

Section I**Manufacturer's Name**

ConAgra Foods

Emergency Telephone Number

1-800-424-9300

Address (Number, Street, City, State, and ZIP Code)

P. O. Box 125
ONE CREATIVE WAY
Rossville, IL. 60963

Telephone Number for Information

1-217-748-6784

Date Prepared

January 12, 2010 (revision of March 26, 2007)

Signature of Preparer (optional):**Section II – Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity: Common Name (s) OSHA PEL ACGIH TLV Other Limits Recommended % (optional))

Chemical Name	CAS No.	OSHA PEL	ACGIH TLV	Other Limits Recommended % (optional)
ISOBUTANE	CAS 75-28-5	NE	NE	
PROPANE	CAS 74-98-6	1000PPM	NE	
BUTANE	CAS 106-97-8	800PPM	800PPM	

Section III – Physical/Chemical Characteristics

Boiling Point	NA	SPECIFIC GRAVITY (H₂O-1)	.817
Vapor Pressure (mmHg)	3102	Melting Point	NA
Vapor Density (AIR – 1)	>1	Evaporation Rate (BUTYLACETATE-1)	>1

SOLUBILITY IN WATER:

SLIGHT

APPEARANCE AND ODOR:

FOAMY PALE YELLOW SPRAY WITH VEGETABLE ODOR.

Section IV – FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT (METHOD USED)	FLAMMABLE LIMITS	LEL	UEL
-100°F ESTIMATED		1.9	9.5

EXTINGUISHING MEDIA:

FOAM, WATER, DRY CHEMICAL, CARBON DIOXIDE, HALON

SPECIAL FIRE FIGHTING PROCEDURES:

KEEP COOL WITH WATER SPRAY, AVOID ROCKETING CONTAINERS

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CONTAINERS GENERATE PRESSURE WHEN HEATED AND COULD CAUSE BURSTING AND DANGEROUS PROPELLING OF CONTAINERS. ALONG WITH VENTING OF FLAMMABLE GAS.

SECTION V-REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID NOT ESTABLISHED
	STABLE	X	

INCOMPATIBILITY (MATERIALS TO AVOID):

OXYGEN AND STRONG OXIDIZING MATERIALS

HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

CARBON OXIDES FORMED WHEN BURNED

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID NOT ESTABLISHED
	WILL NOT OCCUR	X	

SECTION VI-HEALTH HAZARD DATA

ROUTE (S) OF ENTRY	INHALATION? X	SKIN? NE	INGESTION? NE
--------------------	------------------	-------------	------------------

HEALTH HAZARDS(ACUTE AND CHRONIC):

HIGH CONCENTRATIONS IN THE AIR CAN CAUSE A DEFICIENCY OF OXYGEN WITH RISK OF UNCONSCIOUSNESS.

CARCINOGENICITY: NA **NTP?** NA **LARC MONOGRAPHS?** NA **OSHA REGULATED?** NA

SIGNS AND SYMPTOMS OF EXPOSURE:

DIZZINESS, HEADACHE, ETC.

MEDICAL CONDITIONS GENERALLY AGGRAVATE BY EXPOSURE:

NONE KNOWN TO DATE

EMERGENCY AND FIRST AID PROCEDURES:

REMOVE FROM EXPOSURE. IF SYMPTOMS CONTINUE SEEK MEDICAL ATTENTION.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

ABSORB SPILLED LIQUID WITH COMMERCIAL NON-FLAMMABLE ABSORBENT. SHOVEL ABSORBENT INTO DRUMS.

PROTECT FROM IGNITION.

WASTE DISPOSAL METHOD:

DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. CONSULT WITH

APPROPRIATE REGULATORY AGENCY PRIOR TO DISPOSAL.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

STORE BELOW 120° F. IN CASE OF ACCIDENTAL PUNCTURING WITH FORKLIFT, SHUT OFF LIFT AND IGNITION SOURCES VENTILATE AREA.

OTHER PRECAUTIONS:

USE ADEQUATE VENTILATION.

SECTION VIII-CONTROL MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE):

NONE REQUIRED FOR NORMAL HANDLING

VENTILATION ADEQUATE	LOCAL EXHAUST FOR SMALL ENCLOSED WORK AREAS	SPECIAL NA
MECHANICAL (GENERAL) ADEQUATE FOR STORAGE		OTHER NA
PROTECTIVE GLOVES NOT REQUIRED FOR NORMAL HANDLING		EYE PROTECTION NONE REQUIRED FOR NORMAL HANDLING

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

NOT REQUIRED FOR NORMAL HANDLING

WORK/HYGIENIC PRACTICE:

NA