



# ZIPP™

## QUICK DRYING SAFETY DEGREASER

### DESCRIPTION

---

ZIPP™ is a quick drying safety solvent degreaser that instantly removes grease, oil, waxes, tar, gums, grime, dirt, carbon, greasy stains, bilge slime and similar soils from most hard surfaces. It may be used on oil burner parts, compressors, refrigeration units, greasy fan blades, strainers, engines, stoves, relay contact points and electrical equipment. It will not short out electrical equipment.

### CHARACTERISTICS

---

- \* Non-flammable
- \* Fast Drying
- \* Non-conductive
- \* Excellent cleaner/degreaser
- \* Leaves no residue

### APPLICATIONS

---

ZIPP™ may be used to degrease and clean oil burner parts, compressors, refrigeration units, strainers, engines, stoves, fan blades, relay contact parts and electrical equipment.

### PACKAGING

---

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
82642	14 ounce aerosol	12	14	0.52

# ZIPP™ QUICK DRYING SAFETY DEGREASER

## INSTRUCTIONS

**READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING**

**DO NOT USE ON PLASTICS WITHOUT TESTING FIRST**

- For best results, use only on cool surfaces.
- Thoroughly saturate part(s) to be cleaned.
- Spray on small parts with light oil or grease films and on contact points on relays, motors, thermostats, and in all electrical or mechanical equipment.
- For heavy films and tars, allow 5 minutes soaking time, then wipe or flush off.

**For additional technical information, call Toll Free 1-800-231-3345**

## PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**WARNING!  
CONTENTS UNDER PRESSURE. VAPOR HARMFUL  
KEEP OUT OF REACH OF CHILDREN  
READ BACK PANEL CAREFULLY.**

**CONTAINS: CHLORINATED SOLVENTS.** Use only as directed with adequate ventilation. Avoid contact with eyes and skin. Do not spray into fire or on hot surfaces. Store at room temperature. Do not puncture or incinerate (burn) container. Exposure to temperatures above 120° F may cause bursting.

**FIRST AID: Skin:** Wash off with soap and water. **Eyes:** Flush with water for 15 minutes. Seek medical attention if irritation persists. **Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped, and oxygen if available. Call physician immediately.

**For additional information, refer to Material Safety Data Sheet.**

## SPECIFICATIONS

Wt/Gal @ 77°F	11.99 lbs/ gal
Flash Point SETA CC	None
Color	Clear liquid
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

## LIMITED WARRANTY

RectorSeal makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY

RectorSeal • 2601 Spenwick Drive • Houston, Texas 77055-1035  
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051

www.rectorseal.com

E-02